

Manufacturer's Agents to the Middle East & South East Asia

SPRING/ SUMMER 2016




Contents

- 3. Company Overview
- 4. AGS
- 6. Heldite/Kommerling
- 7. Horobin
- 17. Monument Tools
- 35. Backer
- 36. McApline
- 76. Celmac
- 85. Rastelli
- 93. TNJ
- 97. George Lancaster

Company Overview



Contents Page



UK Manufacturing

All our products originate from established British manufacturing companies, producing the highest quality of goods. Where we Operate

We cover the Middle East, Sri Lanka and South East Asia.

W GREER LTD HAS BEEN MANUFACTURING, REPRESENTING AND DISTRIBUTING UK AND EUROPEAN MADE PRODUCTS TO THE MIDDLE EAST AND SOUTH EAST ASIA FOR THE LAST 50 YEARS.

This brochure details some of the more popular products on offer through W Greer Ltd. However, we manufacture, represent and distribute a wider range of products for all types of engineering and retail. For more details contact enquiries@wgreerltd.co.uk and we will be happy to as sist with your requirements all the way through to delivery.





Andrew Greer & Sons (AGS) Ltd

Andrew Greer & Sons (AGS) is a leading producer of high quality anti-corrosion pipe-wrap from the UK. AGS also produce other products such as leaded and unleaded solder wire to the highest standard.

AGSSLDO2 AGS SOLDER WIRE CAPILLARY 3MM



AGSSLD01 AGS LEAD FREE SOLDER WIRE 3MM



AGSFLUX AGS FLUXPASTE

AGS Fluxpaste is a self cleaning Soldering flux used for capillary joints on copper pipework, brass and mild steel.

AGS Fluxpaste is UK WRAS listed for both hot & cold water including potable water.



AGS PTFE THREAD SEAL Tape Conforms to BS7786





12mm or 25mm width. 10m or 12m in length.



'AGS' GREASY PIPEWRAP INSULATING TAPE

An anti-corrosive non-cellulose waterproof membrane based on refined petroleum condensates with added inhibitors and moisture displacement agents. The carrier is a strong non degradable flexi-tape allowing accurate contour contact with virtual elimination of air pockets and loose wrap and ensuring excellent jointseal at overlaps. 'AGS' GREASY PIPEWRAP INSULATING TAPE has been approved and is used by Electricity and Gas Authorities.

Related products to be used in conjuntion with AGS Greasy Pipewrap are:

AGS PRIMER

A single pack coating based on a bituminous wax blend, intended to protect steel surfaces against corrosion. AGS GREASY WRAPPER TAPE PRIMER can be applied by brush, roller or spray prior to the application of AGS GREASY WRAPPER TAPE.

AGS GREASY MASTIC BLANKET

Anti-corrosive cold applied preformed layer of petroleum condensates with added inhibitors and moisture displacement agents. Containing inert siliceous fillers and cellulose fibres. This mastic is backed with a polyester fabric fully impregnated with a petrolatum compound. AGS GREASY MASTIC BLANKETS has been approved and is used by Electricity and Gas Authorities.

Additional protection can be obtained by overcoating with AGS GREASY WRAPPER TAPE.

Packaging

- For more information on any of these products, please email: enquiries@greer-exporting.co.uk 250mm 8 blankets per carton 300mm 8 blankets per carton
- 450mm 4 blankets per carton
- 500mm 4 blankets per carton
- 600mm 4 blankets per carton

AGS GREASY PASTE

A soft mouldable blend of petrolatum and inert fillers containing anti-corrosive inhibitors and moisture displacement agents. AGS GREASY PASTE has been approved and is used by Electricity and Gas Authorities. Packaging 20 litre drums and 5 litre pails.

AGS also supply a cold applied Bitumen PVC Overwrap complete with release paper.







AGS is a market leader in the supply of UK manufactured high quality welded stainless steel tubes.

AGS supply tube worldwide and prides itself on being unique in its ability to offer a range of products and services unrivalled by our competition. This together with our commitment to customer service and satisfaction demonstrates our desire to be the market leader within our field.





Tube EN10312 1.4301 (304) SST 15 - 15mm OD x 0.6mm wt x5800mm SST 22 - 22mm OD x 0.7mm wt x5800mm SST 28 - 28mm OD x 0.8mm wt x5800mm

Other dimensions, grades, specifications and finishes available on request



MANUFACTURING SPECIFICATIONS Tubes manufactured in accordance with BS EN 10296-2:2005 BS EN 10217-7:2005 BS EN 10312 : 2002 ASTM A249 ASTM A269 ASTM 554





"HELDITE" Jointing Compound



Heldite Jointing Compound is a high performance sealant for preventing leakage of Petrol, Diesel Fuel, Hydraulic Fluids, Oils, Paraffin, LPG's, Water, Steam and Gases in all branches of Automotive, Auto mechanical, Electrical and General Engineering, Plumbing, Heating and Pipeline Services

KÖMMERLING



Kommerling Industrial Sealants & Adhesives

Kommerling UK Ltd is a subsidiary of Adco Global Inc, an international group of Companies in strategic locations around the world. It has over 100 years experience in the development, manufacture and distribution of high quality adhesives and sealants for a variety of applications, including Glass, Solar / Photovoltaic, Transportation and General Industrial.

Stag brand Jointing Compounds are manufactured to specific industry standards and are easy release, lead free jointing compounds of smooth consistency for use on flanged or screw threaded joints. These products meet the relevant industry standards for use on pipework carrying water (including potable water), brine, steam, gas (including liquefied and natural gas), fuel oil, diesel oil, petrol or compressed air.

The range includes:

Stag A & B Stag White and Stag White Universal Plasti-Coll X10 and Plasti-Coll X10G Wellseal





For more information on any of these products, please email: enquiries@greer-exporting.co.uk



Steel Test Plugs



- > Available from 40mm up to 450mm diameter.
- Chemical resistant Seals can be supplied to order.
- "Double Seal" plugs can be supplied to order.
- Thrustwashers fitted as standard on all sizes.
- Zinc plated corrosion resistant to 90 hours salt spray test.
- Combines the economy of price with the strength of steel.
- Carries the Horobin name quality guaranteed.
- Nominal pipe sizes, minimum and maximum pipe diameters each Plug will fit, maximum test pressure, and weight of Plug are available on our Web Site.

Aluminium Test Plugs



- Available from 40mm up to 900mm diameter.
- > Aluminium plates combine strength with lightness.
- > Thrustwashers fitted as standard on all sizes.
- > Chemical resistant Seals can be supplied to order.
- "Double Seal" plugs can be supplied to order.
- Steel components are zinc plated to 90 hours salt spray test.
- Carries the Horobin name quality guaranteed.
- Nominal pipe sizes, minimum and maximum pipe diameters each Plug will fit, maximum test pressure, and weight of Plug are available on our Web Site.








Super Nylon Testing Plugs



- Available from 18mm up to 150mm diameter.
- Superior design easier to use.
- > Can be used for testing up to 7p.s.i.
- Designed to fit Telecommunication Ducts for temporary sealing to prevent ingress of vermin and sand.
- Easy to sterilise so can be used in Hospitals, Food Processing Plants etc.
- > Carries the Horobin name quality guaranteed.
- Nominal pipe sizes, minimum and maximum pipe diameters each Plug will fit, maximum test pressure, and weight of Plug are available on our Web Site.

End of Pipe Testing/Sealing Plugs



- > For temporary sealing of new pipework on construction sites.
- > Easier to use than traditional Test Plugs fit flush onto the end of the pipe.
- > Available from 50mm up to 250mm diameter.
- > Can be supplied with or without a Waterway/Airway.
- Zinc plated corrosion resistant to 90 hours salt spray test.
- Carries the Horobin name quality guaranteed.
- Nominal pipe sizes, minimum and maximum pipe diameters each Plug will fit, maximum test pressure, and weight of Plug are available on our Web Site.



MDPE/HDPE Test Plugs for Pressure Testing to 6bar



- > Available for Pipe Sizes from 25mm up to 75mm outside diameter.
- ➢ For use with small bore copper, steel or MDPE/HDPE piping.
- Suitable for Pressure Testing up to 6bar.
- Suitable also for telecommunications, refrigeration, air conditioning, heating, process plant and food manufacturing.
- "Double Seal" plugs can be supplied to order.
- Steel components are zinc plated to 90 hours salt spray test.
- Carries the Horobin name quality guaranteed.
- > Nominal pipe sizes, minimum and maximum pipe diameters each Plug will fit, maximum

Steel Test Plugs (Type 920) Pneumatic Seals



- Multiple compression points around the perimeter of the plug enable the seal to expand in localised areas.
- Strength where it matters at the compression point.
- Steel components are painted against corrosion.
- > The Plugs are fitted with handle bars, to make it easier to locate the plug in the pipe.
- Can be supplied with twin outlets lower outlet allows complete emptying of water from the drain before removal of the plug.
- Chemical resistant Seals can be supplied to order.
- "Double Seal" plugs supplied as standard.





Multi-lock Steel Test Plugs 450mm to 3000mm



- Multiple compression points around the perimeter of the plug enable the seal to expand in localised areas.
- Strength where it matters at the compression point.
- Steel components are aluminium coated against corrosion.
- > The Plugs are fitted with handle bars, to make it easier to locate the plug in the pipe.
- Can be supplied with twin outlets lower outlet allows complete emptying of water from the drain before removal of the plug.
- > Chemical resistant Seals can be supplied to order.
- "Double Seal" plugs can be supplied to order.
- "Instructions for use" label on each plug.
- > Nominal pipe sizes, minimum and maximum pipe diameters each Plug will fit, maximum



- Ideal for use in all types of Plastic Pipe the ridges around the circumference of the Bag prevent the Bag slipping down the pipe. Also designed for use in vertical Soil Stacks.
- Range available for pipe diameters from 25mm to 450mm.
- Easily inflated for trouble free pipe sealing and testing.
- Ideal for use in areas where access is smaller than the test diameter.
- Extension hose available to facilitate remote sealing and testing.
- Nominal pipe sizes, minimum and maximum pipe diameters each Bag will fit, maximum test pressure, and weight of Bag are available on our Web Site.





Canvas Inflatable Air Bags



- The answer to a variety of pipe sealing problems in all Industries from Sewerage, Petrochemicals, Food Processing, Mining etc.
- The Cover is available in Canvas, Heavy Duty Nylon, or Polyurethane coated to resist Petrol, Oil and Diesel.
- Range available for pipe diameters from 50mm to 4,000mm.
- Ideal for use in areas where access is smaller than the test diameter. Can also be supplied with the Inflation Tube in the centre to block off either side of a T.
- Easily inflated for trouble free pipe sealing.
- Fitted either with a Schrader Valve, or Brass Air Tap. Larger sizes fitted with Ball Valve for inflating using a compressor.
- Can be fitted with a Pressure Gauge to prevent over inflation.
- Extension hose available to facilitate remote sealing.
- Nominal pipe sizes, minimum and maximum pipe diameters each Bag will fit, maximum

A.T.O. Inflatable Pipe Stoppers for Air Testing of Sewers



All A.T.O. Inflatable Pipe Stoppers have test and blank ends. 5mm thick closed-cell foam sealing surface. Car type valve for inflation. Pull tag for deflation. No removable parts. Hook and loop strap to attach U Gauge.

PATENT NO.GB2361283 TRADE MARK NO.2299965

Position/pull out handle on 600mm and above.

Nominal bore + or – 6mm.

Size range from 300mm/12" to 1800mm/70".

Manufactured and tested to BSI standard.









High Pressure Inflatable Pipe Stoppers



- Maximum Allowable Back Pressure 3.0 bar (30m head water) **
- Maximum Inflation pressure 6.0 bar**
- Wide expansion range will work in all types of pipe 100mm up to 2,000mm
- · Lightweight, most sizes can be installed by one man
- Reinforced Synthetic Rubber for maximum durability
- Available in Nitrile for Hydrocarbon applications
- Compressor inflation controller
- Specials sizes on request

Socket Testing Devices for Pressure Testing Sockets in Concrete Pipes



- Enables each individual Socket to be precisely tested. Dramatically reduces the amount of water required.
- > Can be supplied in up to 3 sections for Sewers with limited access.
- Suitable for pressure testing drains and sewers to BS.8005 and EN1610.
- Fitted with Wheels so the Device can be easily pushed up the Sewer.
- Superior design and quality ensures ease of use.
- Extension Hoses allow for remote testing.
- We can supply portable Compressors and associated equipment.
- Horobin guaranteed quality.







Drain Testing Kits for carrying out Air Pressure Test to BS.8005/EN1610



- > The complete answer for pressure testing drains and sewers of any diameter.
- HOROBINTM "Drain test Kit" is the only complete kit on the market for pressure testing 100mm drains.
- > Suitable for pressure testing drains and sewers to BS.8005 and EN1610.
- > Superior design and quality ensures ease of use.
- > High visual impact for "Point of Sale" display.
- Horobin guaranteed quality.

Pipe and Drain Tracing Dye



- Tracing Dyes are supplied in 200gram Poly-jars in a range of 6 colours GREEN FLUORESCEINE, RED, BLUE, ORANGE, YELLOW & VIOLET
- Tracing Dye is used for detecting the flow of water in drains or pipes, identifying individual drain runs into a common gully, and tracing leaks in pipes.
- Dyes are non-toxic and odourless. They are approved by the National rivers Authorities, Water Companies and Local Authorities.
- Green Dye contains 50% Fluorescence. The other colours are made from 100% food grade products.
- Use 5ml of Dye per 10 litres of cold water. The best method is to mix the Dye into a bucket of water, and then add to the flow of drain. A 200gram jar will trace up to 15,000 litres in chemical free water.

NEW! We now have a Tracing Dye which is safe to use with Fish. This Dye can be used to trace leakages from Drains, Sewers, Ponds, Reservoirs etc. Sold in 5 kilo drums, which will trace up to 0.5 million litres of fresh water. Mix 500 grams with 10 litres of clean Water.







High Pressure Testing Plug – 6bar+



- For Pressure Testing and Temporary Sealing of Water, Gas, Oil and Sewerage Pipes of any material.
- Ideal for Pressure Testing Sewerage Pipes in accordance with the new European Standard EN1610.
- Pressure Plates are made of aluminium. Rubber Seals are commercial grade rubber mouldings. Thrustwashers are fitted as standard on all sizes.
- Pressure Gauge can be fitted as an option.
- > Chemical resistant rubber seals can be supplied

High Pressure Testing Plug – 2



- For Pressure Testing and Temporary Sealing of Water, Gas, Oil and Sewerage Pipes of any material.
- Pressure Plates are made of steel. The Plugs are fitted with a Ball Bearing Race for ease of tightening. Rubber Seals are commercial grade rubber mouldings.
- Pressure Gauge can be fitted as an option.
- Chemical resistant rubber seals can be supplied

Warning - Appropriate bracing or support must be provided before applying any back pressure in order to prevent the risk of accident.









'Drain Clear' Set

- > Drain Clearance Set in a handy carrying case.
- Ideal for use with short drain runs up to 30m.
- Available with either Universal or Lockfast Fittings. The advantage of Lockfast Fittings is that they cannot come undone down the drain.
- > Ready packed in a strong polypropylene carrying case.
- Set comprises of 30ft of rods, together with 100mm Plunger, Double Worm Screw and 100mm Drop Scraper.
- Horobin quality guaranteed.
- Ideal for use with short drain runs up to 30m.
- Available with either Universal or Lockfast Fittings. The advantage of Lockfast Fittings is that they cannot come undone down the drain.
- Compatible with most other makes of Polypropylene and Cane Rods.
- A wide range of Tools are available such as Rubber Plungers, Worm Screws, Drop Scrapers, Drain and Chimney Brushes.
- Rods available in 19mm, 21mm & 25mm diameter. Lengths are 3ft, 1.5m & 2m.
- Horobin quality guaranteed.

Polypropylene Drain Rods & Tools



Lockfast Steel Rods & Tools



- Ideal for use with long drain runs up to 1 km.
- Manufactured of high tensile steel, with a 2-way locking system which allows the Rods to be rotated both ways.
- > Compatible with most other makes of Steel Rods.

A wide range of Tools are available such as Rubber Plungers, Worm Screws, Drop Scrapers, Crown Root Cutters and Auger Root Cutters.

Rods are available in 8mm and 10mm diameter. Lengths are 1m, 1.5m and 2m.
 Horobin quality guaranteed.



Plumbing & Heating Installation Tools

MONUMENT PIPE CUTTERS - COUPE TUBES - ROHRABSCHNEIDER

ADJUSTABLE SEMI-AUTOMATIC COPPER PIPE CUTTER

COUPE-TUBE AUTOMATIQUE ROHRABSCHNEIDER AUTOMATIK

Order	Dia. Pipes	Display
Code	mm	Pack
300M	8 - 22	V

COPPER PIPE CUTTERS

Order	Dia. Pipes	Dia. Pipes	Display
Code	mm	in OD	Pack
35TC	3 - 35	¹ /8 - 1 ³ /8	\checkmark

			Pipe di	ameters	;	
Order Code	Size	min mm	max mm	min in	max in	Display Pack
264Y	0	4	22 [*]	5⁄32	7⁄8	\checkmark
*264Y can	be used	d for oc	casiona	al cuts o	n 28mn	n
265B	1	4	28	5⁄32	17⁄64	\checkmark
266E	2A	12	43	1/2	1 11/16	\checkmark
TC3	3	25	82	1	31⁄4	

STAINLESS STEEL PIPE CUTTERS

COUPE-TUBES ACIER INOXYDABLE ROHRABSCHNEIDER EDELSTAHL

 	 		_					
		Pi	ре	dia	me	te	rs	

Order Code	Size	min mm			max in	Display Pack
271U	1	4	28	5⁄32	17⁄64	V
272X	2A	12	43	1⁄2	1 11/16	V

PLASTIC PIPE CUTTERS

COUPES-TUBES PLASTIQUE ROHRABSCHNEIDER PLASTIK

			Pipe d	iameter	°S	
Order Code	Size	min mm	max mm	min in	max in	Display Pack
290B	2A	12	43	1⁄2	1 11/16	V
291E	3	25	81	1	3.2	

The use of pipe cutters rather than a hacksaw during installation of pipework avoids swarf entering systems which can cause problems on commissioning. High quality tools for use by professional and DIY plumbing installers, heating engineers and maintenance staff. Each tool assures a square, even cut.

> Cuts automatically once it has been sized and after tightening no further adjustment or feeding of the wheel into the pipe is required.



A strongly made outer ABS plastic casing houses the inside mechanism made from steel which takes the load of the cut.

Made from zinc pressure diecast bodies. All parts liable to wear are heat treated. The fluted handles of sizes 1 and 2A are fitted with a spare wheel.







Fitted with wheels for cutting stainless steel plumbing and other light gauge stainless pipes. Both fitted with spare wheel.



Fitted with wheels for cutting thicker walled plastic pipes such as those used in central heating. No spare wheel fitted inside handle.







For work in confined spaces. Strongly made outer ABS plastic casing houses the inside mechanism made from steel

which takes the load of the cut. Cuts copper pipes once the gate of the tool is closed over the pipe. Tool can be rotated in either direction.




AUTOMATIC COPPER PIPE CUTTERS

COUPE-TUBE AUTOMATIQUE **ROHRABSCHNEIDER AUTOMATIK**

Order Code	Dia. Pipes mm	Nominal Size in.	Display Pack
15PC	15		V
21PC	21	3⁄4	\checkmark
22PC	22		\checkmark
274PC	27.4		\checkmark
28PC	28		V



For work in confined spaces. Cuts in one direction. Only cut the exact sizes of copper pipe specified. Made from zinc pressure diecast bodies.



Two separate handles. Fits where users' hands

or pliers will not fit in confined spaces. Made from bright zinc plated steel and engage in the outer casing of the bodies. Can be neatly

side of the pipe cutter.

slipped on and off from either

MONUMENT AUTOCUT®

COUPE-TUBE AUTOMATIQUE **ROHRABSCHNEIDER AUTOMATIK**

Order Code	Dia. Pipes mm	Nominal Size in.	Display Pack
1715C	15		\checkmark
1721V	21	3/4	\checkmark
1722Y	22		\checkmark
1727N	27.4		\checkmark
1728Q	28		\checkmark

RATCHET HANDLES (to fit Automatic Pipe Cutters and Monument Autocut®)

Order Code	Fits Pipe Cutter	Display Pack
15R	15PC, 1715C	\checkmark
22R	21PC, 22PC, 1721V, 1722Y	V



DISQUES						
SCHNEIDR	SCHNEIDRADCHEN					
Order	Pack	To fit	Display			
Code	Qty		Pack			
To cut Coppe	r pipe					
W15PC	16	15PC, 21PC, 22PC,	V			
		274PC, 28PC				
301P	12	300M	V			
To cut Coppe	r, Brass, Al	luminium, Light Gauge Steel F	Pipes			
273A	12	264Y, 265B, 266E, TC3	V			
To cut Stainles	s Steel Plu	umbing pipe, Golf Club Steel S	hafts			
284I	12	264Y, 265B, 266E, TC3	\checkmark			
To cut Plastic	ріре					
310R	10	264Y, 265B, 266E TC3	V			
To cut 15 & 22mm Copper pipe						
269N	16	1715C, 1721V, 1722Y,	V			
		1727N, 1728Q, 35TC,				
		Pipeslice®				

Monument pipe cutter wheels are made from high quality, correctly heat treated steels.

mon



PLASTIC PIPE CUTTERS

Order Code	Max size mm		Display Pack
2640E	25		V
2645T	42	Ratchet	V
2647Z	60	Ratchet	V

DE-BURRING TOOLS

EBAVUREUR

SCHNEL	LENIGR	AIEK
Order	Display	
Code	Pack	
3020C	V	
Order	Display	
Code	Pack	
2117Q	\checkmark	De-burring tool
2118T	√ (10)	Spare blade- Steel & Aluminium
2119W	√ (10)	Spare Blade- Brass & Cast Iron

COPPER PIPE END CLEANER

OrderSizeDisplayCodemmPack364C15✓

COPPER PIPE END CLEANER & DEBURRER

Order	Size	Display
Code	mm	Pack
DBB1522	15 & 22	V

INTERNAL & EXTERNAL COPPER PIPE END DEBURRER

Order	Size	Display
Code	mm	Pack
365F	42	\checkmark

WASTE PIPE DEBURRER

Order Code	Size nominal in	Display Pack
3026U	11/4	V
3027X	11/2	V

BRUSHES FOR CLEANING FITTINGS BROSSES POUR TUBE

ANBRINGEN VON REINIGUNGSBÜRSTEN


Order Code	Size mm	Display Pack	Use
3021F	15	V	15mm fittings
3022I	22	\checkmark	22mm fittings
3023L	28	\checkmark	28mm fittings

COPPERKEY®

Order	Size	Display	Use
Code	mm	Pack	
2915Q	15	V	15mm pipe & fittings
2922M	22	V	22mm pipe & fittings

Very effective on PVC, polybutylene, MDP, polyethylene, HEP₂ O^{\otimes} , plastic overflow pipe, plastic electrical conduit, supertube, mini trunking, rubber hose, pneumatic pipe, electrical sleeving.

NEW



Replaceable Blade type. Similar specification to above but button release for renewable and changeable blades. Metal body.

Disposable. Cleans the outside of copper pipe with a few turns prior to soldering.





Cleans and de-burrs 15 and 22mm copper pipe. One size at each end of the tool.

De-burrs internally and externally up to 36mm copper pipe






Cleans and de-burrs plastic waste pipe. For push fit plastic pipe



Made in

Britain

For cleaning the inside of copper fittings and socket formed joints on copper pipe prior to soldering. Stiff steel bristles.



Patented ratchet handle makes jobs possible in all tight spaces. Eliminates the risk of scrapes or flux burns.



For more information on any of these products, please email: enquiries@wgreerltd.co.uk

Pack of 3 brushes with loop handle and nylon bristle heads

180 grit silicone carbide strips of abrasive waterproof open mesh material for tough cleaning jobs. For roughing up plastic pipe, cleaning inside fittings (can be cut into small strips), deburring metal and wood surfaces.

> Medium grade 50 mm x 250 mm pads for cleaning, polishing, rust removal, scrubbing and blending. Washable, will not rust and does not break up during use.

Designed to remove an olive from copper pipe without damage to the pipe and without producing swarf.

Carbo nitrided carbon steel cutting blades. Specifically designed to remove copper and brass olives. Do not attempt to remove stainless steel olives with this tool.

> Patented tool for removing 15mm, 22mm and 3/4" olives. Engages with 14tpi thread of the compression fitting.

For joining two pieces of copper pipe of equal diameter together without using fittings. The resulting capillary joint can be soft or hard soldered. The loose socket former allows easier withdrawal of tool after use.



FLUE BRUSHES

Order	Length	Size	Display
Code	mm	mm	Pack
3014J	405	Ø16, Ø50, 50x16 rectangular	V

ABRASIVE CLEAN-UP STRIPS 0 Display

Order	
Code	
0240	

30

Pack √(10 Strips)

CLEANING AND POLISHING PADS

Order	Display
Code	Pack
3025R	√ (5)

OLIVE REMOVING TOOLS

OLIVE CUTTERS		
Order	Copper	pipe dia.
Code	mm	in
2034N	8	
2033K	10	
2030B	15	1/2"
2031E	22	

2031E will not fit 3/4" Imperial olives

OLIVE PULLER

2036T	15, 22	3⁄4"	
-------	--------	------	--

COPPER PIPE JOINTERS / SOCKET FORMERS

OUTILS A FORMER LES EMBOITEMENTS MUFFENFORMER

Order Code	OD mm	Wall mm	Display Pack
131W	15	0.7	V
133C	22	0.9	V
134F	28	0.9	
220S	15	1.0	\checkmark
222Y	22	1.2	\checkmark

15 & 22mm COMBINATION SOCKET FORMER

Order	OD	Wall	Display
Code	mm	mm	Pack
138R	15, 22	0.7, 0.9	\checkmark

FLUX BRUSHES

,	Order	Length	Size	Display
	Code	mm	mm	Pack
	3015M	195	10	\checkmark

COPPER PIPE JOINTING SET

OUTILS A FORMER LES EMBOITEMENTS MUFFENFORMER

Order	OD
Code	mm
139U	15, 22, 28



Soft bristles. varnished handle. Pack of 3

INTERNAL BENDING SPRINGS

RESSORTS A CINTRER LES TUBES KUPFERROHR-BIEGEFEDER

Order	OD	Wall	Colour		
Code	mm	mm	Code		
828 O	8	0.6	Gold		
827L	10	0.6	Gold		
829R	12	0.6	Gold		
830V	15	0.7	Gold		
832B	22	0.9	Gold		
833E	28	0.9	Gold		
834H	35	1.2	Gold		
Order	OD	Wall	Colour		
Code	mm	mm	Code		
840A	15	1.0	White		
841D	22	1.2	White		
877K	28	1.2	White		
878N	35	1.5	White		
843J	20	Conduit Spring			

EXTERNAL BENDING SPRINGS

Order Code	Pipe dia. mm OD.	
888S	8	Round section wire.
889V	10	Round section wire.

MONUMENT COPPER PIPE BENDER

CINTREUSE POUR TUBES ROHRBIEGEMASCHINE

Order	Copper Pipe	Stainless steel
Code	Size mm	Size mm
2600K	15 & 22	15

PIPE BENDER SPARES

Order Code		Display Pack
2601N 2603T	15mm guide 22mm guide	\checkmark
26057	Hook Stop	

20052	поок згор		
2609L	15mm Former		
2610P	22mm Former		

Guides will fit some alternative manufacturers pipe benders.

MINI PIPE BENDER

Order Code

2611S 2612V Copper Pipe Size OD 6mm, 8mm, 10mm 1/4", 5/16", 3/8" Square section spring steel for internal bending of copper pipes. Polished finish.

Used to bend copper pipe externally. Useful when a number of different bends are needed in a long length of pipe.


Made in

Britair

For BSEN1057 15mm, 22mm copper pipe



For 180deg bends on 6mm, 8mm and 10mm copper pipe



Made for igniting LPGas and welding torches. Cup shaped shield traps the gas and assures ignition.



....



For soldering & brazing of copper, brass, aluminium. Use with propane/MAPP[®] gas. Piezo ignition. Hot turbine flame. Flame lock button. Flame adjustment valve. Ergonomic hand grip.



Adaptor 3445R connects 3440C to Calor[®] 340 & Primus[®] 2000

The H2&O Wet & Dry Test Kit has been designed to offer the professional plumber & installer the equipment to pressure test most common applications with its selection of connectors and gauges

Pressures of up to 25 bar can be read from the Gauges with an accuracy of +/- 2.5%. Each gauge is protected with a high shock absorbing rubber boot cover.

Additionally a peak reading needle allows for readings to be taken when the gauge is left unattended Connections to copper or plastic tube (15mm & 22mm) or

thread ($\frac{1}{2}$ "bsp & $\frac{3}{4}$ "bsp) can be made with the selection of adaptors

A 10 bar flexible hose also allows for testing in confined or restricted areas

System filling can be achieved with the aid of the 3/4" tee piece

FLINT SPARK LIGHTERS OR STRIKERS

ALLUMEUR A PIERRE A FEU FEUERSTEINANZUNDER

Order Code	Display Pack
3418L	V
Spare Flints	
3421V	√ (5)

TRIGGER TORCH



		Display Pack
2	Trigger torch Adaptor fits Primus® 2000 & Calor® 340	v v
: J	Gas torch-sealing washer Tip end for 3440C	v v

WET AND DRY TEST KIT

Order Code	
1514R	

Kit Contains:

1 x Plastic Carry Case

1 x Dry Test Gauge 63mm diameter

(0-4bar) x 15mm JG Speedfit™

c/w Schrader Valve test point

fitted with Peak Reading Needle

1 x 63mm diameter Pressure Gauge (0-11 bar) fitted with Peak Reading Needle

1 x 63mm diameter Pressure Gauge (0-25 bar) fitted with Peak Reading Needle

- 3 x Rubber Gauge Boots fitted to above
- 1 x Rubber Tap Connector
- 1 x 10 bar Flexible Hose
- 1 x Gauge Adaptor

1 x PVC covered chain c/w 2 screws & washers

- 1 x CP Reducing Bush 3/4" x 1/2"
- 1 x |G Speedfit[™] 15mm x ¹/2" stud
- 1 x |G Speedfit[™] 15mm x ¹/2" stem
- 1 x |G Speedfit[™] 22mm x ³⁄4" stud
- 1 x JG Speedfit[™] 22mm x ³⁄4" stem
- 6 x O rings
- 1 x Filling Tee Adaptor $\frac{1}{4}$ "



MOPITUP®



Pack of 3 sheets

The versatile super absorbent sheet. The quick, easy and effective way to clean up all water based spillages in the home or workplace. Each 370mm x 370mm sheet absorbs up to 2 litres of water

Mopitup® will ONLY absorb water based fluids. Can be placed ONTO spilt water by turning it so the plastic side is upper most and the net is towards the water spill. Can be placed INTO water containers and will "suck" out the water i.e. draining cisterns, drains, holes. The 'gel' formed is non toxic and safe (but note that the contents are only safe NOT the additive contaminant).



Ideal for :

- plumbing emergencies and repairs
- dripping radiators
- radiator and pump removals
- · leaking pipes, toilets and basins
- · overflow leaks in roof tanks
- · leaking hot water tanks
- fridge and freezer defrosting
- large floor spillage
- protection for carpets and floors
- · draining header tanks
- no drips, no mess, no stains
- water is 'locked' in and cannot be squeezed out, unlike a sponge

Designed to protect surfaces from deflected

heat surrounding a soldering operation. Even after outer fabric breakdown occurs the infill will prevent any thermal transfer withstanding temperatures up to 1260°C

FLAMEBARRIER PAD

Order	Size		Display
Code	in	cm	Pack
2353G	11 x 8	28 x 20	V

SOLDERING AND BRAZING PADS

PARE FLAME						
LOT UND	LOT UND HARTLOTKISSEN					
Order	Squ	are	Display			
Code	in	cm	Pack			
Woven glass fabric. Professional quality						
2350X	12 x 12	30 x 30	\checkmark			

Order Code	Squ in	are cm	Display Pack
HDW graph	ite, woven gla	assfibre	
2351A	10 x 10	25 x 25	\checkmark

Order	•		S	lize		Display
Code		i	in		cm	Pack

Asbestos free (heavy duty) mat Professional quality soldering & brazing mat 23480 12×10 30 x 25

O-MAT®

Order Code	Pipe Size mm	Display Pack
2355M	15 to 22	V
2356P	28 to 50	V
2358V	50 to 100	\checkmark



of the pad.

Provides protection to fixtures and fittings when soldering. Made from non-asbestos glass fabric.

For protection of surrounding areas

when soldering etc. both these pads


resist temperatures up to 600 deg.C and do not present any of the hazards associated with asbestos

materials.



Heat should not be concentrated for long periods on the same area





Patented variable cut out mats for soldering pipes. Reduces the risk of fire. Protects walls, cables, carpets and other flammable materials. The unique shape with overlap gives a tight and secure fit.





For fixing toilet pans to the floor



Used for opening up lead pipe prior to joint wiping. Made from polypropylene.

Used for wiping lead

soldering. Made from best quality moleskin cloth, 6 ply thick. Properly folded with oilboard layer and securely sewn.

joints during

SCREWDRIVERS



Size 300mm blade length 450mm blade length

TURNPINS

TOUPIES ROHRAUFWEITER

Order	Base Dia		Display
Code	in	mm	Pack
602E	11/2	38	V
604K	2	50	V

WIPING CLOTHS

Order	Siz	ze	Display
Code	in	mm	Pack
551W	2 ½ x 1½	63 x 38	V
552Z	3 x 2	75 x 50	V
556L	3½ x 2½	88 x 63	V
558R	4 x 3	100 x 75	V
560Y	4 ½ x 3½	114 x 88	V
563H	5 x 4	125 x 100	\checkmark

MOLESKIN

MOLESKINE

MOLESKINTUCH			
Order	Size	:	
Code	in	cm	
570D	39 x 36	100 x	

72 j	36 x 10	

TALLOW

SUIF			
TALG			
Order Code		Approx kg	
261 P	Plastic tub/outer	0.25	Small
262S	Plastic tub/outer	0.50	Medium
263V	Plastic bucket	4	Large
260M	Box/polythene liner	12.5	XL

91

91 x 25




honument TALLO

> Used for packing and insulation. Asbestos free. For operational temperatures up to 600 deg C. Resistant to oils, most chemicals and solvents and is unaffected by bacterial growth. Constructed from a thick glass yarn wall coupled with a stranded centre glass yarn core. Ideal for use in dry, static sealing applications involving hot air and combustion gases. Supplied on reels.

GLASSFIBRE YARN

Order	Diameter		Approx length per reel	
Code	in	mm	metres	
2330N	1/4	6	25	
2331Q	5⁄16	8	25	
2332T	3⁄8	10	25	
2333W	1/2	12	25	
2334Z	3/4	19	25	

Made in Britain








Best quality white moleskin cloth, closely woven. Approx 36in. 91cm wide

Used as a lubricant for threading,

pulling electric cables through conduit etc. Best quality hard white tallow.





For more information on any of these products, please email: enquiries@wgreerltd.co.uk

Made in



Die-cast aluminium handle and square section tubular steel frame combine to give a lightweight tool with great tensile strength. Adjusts to give 45° angle for flush cutting. Supplied with 24tpi 12" 300mm blade.

Junior hacksaw with finger guard and 32tpi blade.

For drilling holes in timber joists etc.

Very thin 42tpi blade for accurately cutting all kinds of materials including ferrous materials. Wooden handle.

For use on stainless steel, cast iron, mild and galvanised steel, aluminium, copper, brass, plastics and wood. High quality tools with M42 Cobalt High Speed Steel Cutting blades with variable pitch teeth.

Holesaws with integral shank and pilot drill supplied with a split point HSS pilot drill which reduces skidding on convex surfaces, eliminating the need for pre-punch.

Depth of cut 32mm (double depth if the work is reversed). Do not exceed recommended working speeds, as shown in table opposite.

ESSENTIAL LUBRICANTS :

When cutting mild steel (incl. aluminium, copper, brass, zinc, plastics, wood) no lubricant is necessary.

When cutting cast iron use paraffin. When cutting stainless steel use Cutting Compound.



HACKSAW

SCIE A METAUX

KLEINSAGE

Order Code	in	mm	Display Pack
1921D	12	300	V
HSS Blades	24 tpi		
1922G	12 x ½	2 x 0.025in	
	300 x ⁻	13 x 0.65mm	√ (10)

JUNIOR HACKSAW

Order Code	Si	ze	Display Pack
2000M	6in	150mm	\checkmark
Blades 32 t	рi		
1120U	x 1⁄4 x	0.015in	√ (10)
	150 x	6 x 0.38mm	

SPADE BIT SET

Order Code	Sizes	Display Pack
1950P	10mm, 12mm, 16mm,	V
	18mm, 20mm, 25mm	

RAZOR SAW

Order		Display
Code	Size	Pack
1952V	165mm	\checkmark

MONUMENT HOLE SAWS

SCIES-CLOCHES – LOCHSAGEN

Order	Dia.		•		Stainless	
Code	mm	Use	steel	iron	steel	Pack
10mm shar	nk. Or	ne piece holesaw	rpm	rpm	rpm	
1848E	22	¹ /2in BSP	390	260	195	V
11.5mm sh	ank. C	One piece holesaws				
1849H	28	³ /4in BSP	300	200	150	\checkmark
1850L	35	1in BSP	245	165	125	\checkmark
1851O	45	1 ¹ /4in.BSP	190	130	95	\checkmark
1852R	50	11/2in.BSP	160	105	90	V
1853U	64	2in BSP	130	85	65	\checkmark
1857G	70	2¾in Soffit Board Ventilator	115	75	55	V

1899G

Plumbers Holesaw Kit with 22mm 28mm 35mm 45mm 50mm 64mm holesaws with integral shanks. Includes 2 drills and screwdriver and display box.



RAPID-DOSE®

	52
Order Code	
611 G	Filling loop tool
621L	Universal dosing kit
612J	Radiator dosing point
Radiator ven	t pin adaptors
617Y	M6 for Barlo® radiators
623R	M5 for Stelrad [®] radiators
625X	M4 for Myson [®] radiators
626A	Grundfoss® circulating pump dosing adaptor
628G	Wilo [®] Terrier [®] Dab [®] Circulating pump
0200	dosing adaptor
613M	RAPID DOSE Tool kit
630N	Central heating protector. Protects against
	scale, corrosion & bacterial growth. 200ml
	can treats 5 radiators.
632T	Pre-commissioning cleaner. Removes flux
	residues, greases, oily contaminants, sludge
	and debris 400ml can treats 10 radiators.
633W	Non Acid Sludge Dissolver. Dissolves sludge
	and restores heat and flow. 400ml can treats
	10 radiators
634Z	400ml Central Heating Protector
635C	Inhibitor Test Kit. Tests the concentration



Inhibitor Test Kit. Tests the concentration level of inhibitor. 40 tests per kit.

Dose a sealed system within a matter of minutes with **RAPID-DOSE**

- No need to draw off water, release system pressure or wait for system to cool
- Specifically designed to meet the requirements of modern condensing boilers
- Discharges in under a minute
- Suitable for all metals including aluminium
- No mess.

How does RAPID-DOSE work?

RAPID-DOSE works by holding the product (inhibitor or cleaner) in a bag inside the canister. This separates the product from the propellant and means that although the product is squeezed out of the bag by the pressure, the propellant never leaves the canister. As the pressure in the canister is greater than system pressure, the canister rapidly discharges into the heating system.

RAPID-DOSE

Filling

Loop

Tool

THE EASY WAY TO DOSE SEALED **HEATING SYSTEMS**

Aqueous Logic is revolutionising water treatment with a new dosing system designed to make water treatment easier and less expensive. RAPID-DOSE is a disposable pressurised canister, pre-filled with inhibitor (or cleaner), that can be used to dose a sealed system within a matter of minutes. There's no need to release system pressure or draw off water. Simply connect the canister to the filling loop isolation valve, radiator dosing point or circulating pump dosing point using the purpose designed RAPID-DOSE connector, and the canister will discharge itself.

611G

Universal Dosing Kit. Allows Rapid-Dose cans to be discharged directly into the filling loop or radiator vent point



Circulating Pump

Radiator vent pin adaptors. Add a permanent Rapid-Dose dosing point by adapting a standard radiator vent point

Radiator Dosing Point. Add a permanent Rapid dose dosing point by replacing a blank in a four connector radiator

623R

625X

621L

628G

Made in Britair

Boxed kit contains: 1x 621L Universal Dosing Kit 1x 612| Radiator Dosing Point 3x Radiator Vent Pin Adaptors (M4 M5 M6) 1x 626A Pump Dosing Point 1x 3mm Allen Key



FLITZ METAL POLISH

FLITZ TS010 FLITZ BP03509 FLITZ BP03511 FLITZ BU03515-F	Order Code
FLITZ BP03511 FLITZ BU03515-F	FLITZ TS010
FLITZ BU03515-F	FLITZ BP03509
	FLITZ BP03511
	FLITZ BU03515-F
FLITZ CA03518-6	FLITZ CA03518-6

Size	Туре
0.20	<i>,</i> ,
2g	Trial Size
10g	Blister Tube
50g	Blister Tube
150g	Boxed Tube
906g	Tin

Pack

Display

Pack

1

 \checkmark

613M

Flitz Paste Metal Polish is a concentrated cream which cleans, polishes, de-oxidises and protects brass, copper, silver plate, chrome, stainless, nickel, bronze, gold, aluminium, painted surfaces, glass. Removes tarnish, water stains, chalking lime deposits, heat discolouration, oxidation, tar, oil, tree sap. Nonabrasive, non-toxic, non flammable.

Drain Cleaning Equipment

DUAL ACTION FORCE PUMP

Size

Small

Large

Order Code

_	I		
_			

1457Q Medium

FORCE CUPS Order

1454

Code

1456N

1458T

PLUNGER

Order

Code

1459W

Order

Code

M-M3

Order

Code

MP1600

MINI PLUNGER

Display Pack \checkmark

in

3

4

43/4

Display

Pack

 \checkmark

Display

Pack

 \checkmark

Diameter

mm

75

100

120

Length

mm

115

255

405

Display

Pack

<

All plastic force pump with two interchangeable cups, one for clearing blocked sinks, wash

basins, showers, baths and urinals, the other for WCs.



Popular tools for clearing sink, basin

and bath wastes

For kitchen sinks, waste disposal units and showers. Exclusive patented bellows design; more cubic centimetre displacement than traditional force cups; easily cleaned, removable handle

> For small hand basins. Exclusive patented bellows design; more cubic centimetre displacement than traditional force cups; easily cleaned, removable handle

> > For toilets and gulleys. Exclusive patented bellows design; more cubic centimetre displacement than traditional force cups; easily cleaned, removable handle

For small hand basins. Exclusive patented bellows design; more cubic centimetre displacement than traditional force cups; easily cleaned,

> Made **Brita**i

Ideal for clearing WC pan wastes and gullies with soft, flexible rubber and wooden tee handle

Made with flexible rubbers and zinc plated steel components suitable for suction clearing of drains and gullies.

Galvanized steel wire with gripping handle for clearing sink, shower and bath wastes.

SUCTION OR COOPERS PLUNGER **D** I I **A** D.

Order	Rubber Dia		
Code	in	mm	
1453E	5 ½	140	

RUBBER PLUNGERS

	Plu	inger		
Order	dia	neter	Handle	length
Code	in	mm	in	cm
184E	4	100	30	76
185H	6	150	30	76

SINK WASTE CLEANER

Order	Lei	ngth	D	ia	Display
Code	ft	m	in	mm	Pack
909L	6	1.8	1⁄4	6	V
910P	12	3.6	1⁄4	6	\checkmark

TOILET PLUNGER Display Pack \checkmark

HANDY PLUNGER

Order	Display
Code	Pack
1460Y	V

Pack \checkmark



Sets are supplied with rods and fittings as indicated, each set with straps.

DRAIN CLEARING SPRINGS

Order Code	Ref	Length ft x in.	Dia. m x mm	Display Pack
For sinks, bat	hs, showers	small pipe	S	
3343H	15PQH	15 x ¼	4.5 x 6	V
3344K	25PQH	25 x ¼	7.5 x 6	V
For larger pip	es 2-3in 50	-75mm		
3347T	50PMH	50 x 3⁄8	15 x 10	\checkmark
DRAIN UN	NBLOCK	ERS		
Sinks, baths, s	howers, sma	all pipes		
Order Code	Ref	Length ft x in	Diameter m x mm	Display Pack
Steel containe	er			

	•			
3313S	25SM	25 x 1⁄4	7.5 x 6	\checkmark
Plastic conta	iner			
3315Y	20PL	20 x ¹ ⁄4	6 x 6	\checkmark
C-25PL	C-25PL	25 x ¹ ⁄4	7.5 x 6	\checkmark
3316B	Spare Lo	ocking Scr	ew Assembly	

DRILL SNAKE

Order Code 3351G 15' 4.5m Effective length 3351G-CLUTCH Spare Clutch for 3351G

TOILET PAN UNBLOCKERS

Order			ngth	D	Dia	Display
Code	Ref	ft	m	in	mm	Pack
3349Z	3NKH	3	0.9	3⁄8	10	\checkmark
3350D	6NKH	6	1.8	3⁄8	10	V
3354P	3FL	3	0.9	1⁄2	12	\checkmark

Also see page 38

STEEL DRAIN RODS

Order Code	Len ft	gth m	Roc in	l Dia mm	Rods in set
Ths set includ joint; Key; Ha			0		or to universal e.
9081	6	1.8	1⁄2	12	2
Spares for 1/2i	n 12m	m sets			
Order Code					
903T	Spare	e 3ft 0.9m	n Back	length	
904₩	Ferre	et Starter	3' x '	1/2"	
905Z	Ferre	et Handle	1/2"		
906C	Ferre	et Key 1/2	<u>o</u> "		
907F	Ferre	et Adapto	r 1/2"	to Ur	niversal Joint Cane
T I (II)					

The following sets include Handle; Key; Double worm screw; 4in 100mm Plunger & Drop scraper

893I	30	9	3⁄4	19	10
892F	60	18	3⁄4	19	20
pares for	³ ⁄4in 1 9 m	nm sets			
895O	Spar	e 3ft 0.9	∂m rod		
896R	4" 1	00mm [Drop Sc	raper	
897U	Clea	ring Wł	neel		
898X	Dou	ıble Woi	rm Scre	w	
899A	4" 1	00mm F	lunger		

Key

Handle Adaptor 3/4" to Universal Joint

Made in Britain

902O

Compact, lightweight water ram uses a burst of compressed air to produce kinetic transfer of energy through water to break up blockages in pipelines. Ram has safety valve, self contained air pump and gauge to read correct working pressure. Works on wash basins, showers, baths, sinks, urinals and drains.

Strong, lightweight,

of cover. Patented

simple means of removing most types

design.

3298R

KINETIC WATER RAM

Order Code

3336L Complete with 1¹/₂", 2", 3", 4" (38, 50, 75, 100mm) plugs; 5 bungs 1/2" to 3".; 7" 175mm WC cleaning disc; water filling and caulking hoses; tap connector; carrying case; instructions; couplings & connectors.

Set of 5 bungs 3337P

PANGO® PROFESSIONAL POWER PLUNGER

1621R Complete with adaptors to fit most sinks, basins, bidets, baths & showers. Plastic construction. 15 pumps gives approx 3bar of pressure.

MANHOLE LIFTERS

Order	Length		
Code	in	mm	
Manufactured	from	duc	

ictu	red from	ductile	iron
U	34	910	

~		~	4 4 4 4 4 1
Spare	head	tor	1013U

STANDPIPE KEY

1013

1017G

Order	L	L
Code	in	m
3298R	36	1

For opening & closing fire hydrant valves. 2" tapered opening.

STANDPIPE

Order Code 3299U

³/4" Contractors Standpipe. Complete with hydrant base, double check valve and single $\frac{3}{4}$ " tap outlet

GULLEY KEY



MONUMENT TOOLS

MANHOLE COVER LIFTING KEYS


Order Code	Ler in	ngth mm	Handl in	e width mm		End shape
						Shape
Malleable i	ron. Iee	nandie	9			
1010L	5	125	4	100		D
For light d	uty man	hole c	overs			
1012R	8	200	4	100		
Closed har	ndle				Size mm	
MLK06	5	150	4	100	35x15x4	
MLK12	12	300	4	100	35x15x4	
MLK20	20	500	4	100	35x15x4	
MLK24	24	600	4	100	35x15x4	

All manhole cover lifting keys are sold in pairs



Clears blocked and slow running sinks, basins, baths and showers. No chemicals Pressure Relief Valve

Comprises four different key heads designed to locate into most keyholes.



SAFE LIFT MANHOLE COVER LIFTING SET

Order Code 1030V

Ref DDK1MON Safe Lift Kit

The 'Safe Lift' kit includes: Pairs of : Heavy duty quick release lifting handles, 23mm & 35mm wide drain keys, 7mm rounded hooks, 8mm & 10mm & 12mm diameter threaded screw-in tips. Carry case.

Spares for 'Safe Lift' kit.

Order			
Code	Ref	Size	Use
1031Y	DDK1	Heavy dutyquick r handles	elease lifting
1032B	T1004	23mm wide drain key	Slotted light duty covers
1033E	T1001	35mm wide drain key	Slotted heavy duty covers
1034H	T1006	7mm rounded hook	Light duty covers with key holes
1035K	T1007	8mm diameter threaded screw-in tip	covers with threaded lifting points
1036N	T1008	10mm diameter threaded screw-in tip	covers with threaded lifting points
1038T	T1009	12mm diameter threaded screw-in tip	covers with threaded lifting points
Accessorie	es		
1040A 1042G	E1001 B1001	Extension handle Bottle jack	

 Monument 'Safe Lift' manhole

 Nonument 'Safe Lift' manhole

 vuty quick release tip system,

 interchangeable tips, 3 lifting

 popping facility. Additionally, the 'Safe

 ift' features include one piece stainless

 steel tips ergonomically designed

 comfortable lifting handles and an optional

 extension handle.

The optional extension handle incorporates a crow bar style tip to facilitate lifting of covers, can be used to extend the standard heavy duty quick release handle and also, when used in conjunction with a bottle jack, to 'pop' stubborn covers.



HYDRAULIC MANHOLE COVER LIFTER

Order Code



Hydraulic manhole cover lifter Spreader Bars



Hydraulic manhole cover lifter is quick to assemble and simple to use. The lifter can give up to 1.5 tons of lift, making easy work of the heaviest manhole cover. The lifter is supplied with 4 sets of keys which will enable most types of cover to be lifted. Weight 25kg.

Made in

Britair

Also available are spreader bars which enable 4 keyhole covers to be lifted. These bars also have a seal breaker which help ease covers which have not been lifted in a long time.



MONUMENT TOOLS

Handy Snakentainer helps eliminate messy floors when cleaning out blocked small pipes. Collet chuck tightens firmly on cable with a quarter turn. Rotation by electric drill or crank handle whilst holding rotating hand grip. Durable steel container can hold up to 25' x 3/8" or 50' x 1/4" cable.

Rotary Handle - Instead of using the Snaketainer above, the handle with two smoothly operating hand grips will fit all the cables shown on the left. The locking screw of the handle fixes the cable in position whilst rotating.

All GENERAL professional quality hand tool cables have a 42 strand wire rope centre. Coiled right handed to make manual operation easier through greater flexibility.

A large crank handle at the back of the drum gives powerful leverage. After a few turns the speed and momentum breaks through the most obstinate blockages. Rust resistant treated steel drum with carrying handle fitted.

PROFESSIONAL DRAIN UNBLOCKERS

Rotary Handle



3311M D-25-0 Empty Container with Electric Drill attachment. Fits cable 3318H, 3319K, 3320O, 3322U.

	 0
 _	 <u> </u>

Fits all the cables shown below

Order Code	ft	Length in	x Dia m	mm	Ref
Sink traps; s	howers	; basins			
3318H	25 x	1/4	7.5	x 6	L-25FL1
11/4in 35mm	wastes	5			
3319K	50 x	1/4	15	x 6	L-50FL1
Heavier duty	- small	pipes			
33200	25 x	5⁄16	7.5	x 8	L-25FL1-A
1¼ - 3in 35	- 75mr	n pipes			
3322U	25 x	3⁄8	7.5	x 10	L-25FL2

Order Code Ref

3334F

400 **Empty Spin-Drive Snakentainer**

Cables for use with Rotary Handle or Spin-drive Snakentainer 11/4 - 3in 35 - 75mm pipes

3323X	50 x 3⁄8	15 x 10	50FL2
3 & 4in 75 a	& 100mm pipes		
3324A	25 x ½	7.5 x 12	25FL3
3325D	50 x ¹ /2	15 x 12	50FL3

TELESCOPING TOILET PAN UNBLOCKER

Order Code T6FL-DH

6' 1.8m Effective length

MONUMENT TOOLS

KYNA-COLT KINETIC RAM

Order Code



33370 Kyna-colt in toolbox with 2 toilet discs, 3 expanding plugs and tap connector. No bulbs supplied

3338R Spare Carbon Dioxide bulbs. Approx. 45 psi





the first 3' 0.9m into a WC pan or gully there is a further equal length of cable telescoped inside the guide tube operated by pressing a button and pulling back the crank handle. Double spring Flexicore cable with vinyl guard to avoid scratching WC pans.


Made specifically for the difficult

blocked WC pans. After working

job of removing solid objects from

Compact, lightweight water ram uses a burst of compressed air from a carbon dioxide bulb to produce kinetic transfer of energy through water to remove blockages in pipelines. Ideal for "soft" blockages such as those normally encountered domestically caused by organic matter e.g. paper, hair, fat, grease, general kitchen waste, plastic cups, towels, uric acid and soft lime scale etc.

For more information on any of these products, please email: enquiries@wgreerltd.co.uk



Press

DOWN HEAD

	TOWER DRAIN CLEANER COTTARISON CHART						
		Typical Applications	For use in following Pipe Sizes	Maximum Capacity	Operating Re Weight	Maximum ecommende Distance	d Motor Horsepower
•	SUPER-VEE POWER-VEE HANDYLECTRI PH DRAIN ROOTER	Sinks Bath Wastes C Roof Stacks	1¼" - 3" (35 - 75mm)	35' x ³ ⁄8" or 50' x ⁵ ⁄16" (10.5m x 10mm or 15m x 8mm)	7kg with 25' x 3/8" (7.5m x 10mm)		2.7 A
•	MINI-ROOTER MINI-ROOTER XP	Small drains, Inside work, On roofs (Not for roots)	1 ¹ /4" - 3" and most 4" (35 - 75mm and most 100mm)	75' x ½" (23m x 12mm)	23kg with 75' x ¾" (23m x 10mm)	75' (23m)	¹⁄₃HP
•	SEWEROOTER T-3	Small drains, Inside work, On roofs (Not for roots)	11⁄4" - 3" and most 4" (35 - 75mm and most 100mm)	100' x ½" (30m x 12mm)	52kg	100' (30m)	⅓ HP
•	METROROOTE	R Roots and scale	e 3"-6"	75' x 5/8" (23m x 16mm)	76kg	75' (23m)	1/3HP
•	speedrooter 91	Combination Sewerooter T-3 and Maxi-Rooter	2" - 10" (50 - 250mm)	100' x ¾" or 100' x ½" (30m x 19mm or 30m x 12mm)	108kg	200' (60m)	¹ ⁄2HP (Optional ³ ⁄4HP)
	MAXI-ROOTER	Heavy Duty Roots, Sand, Rags Grease, Lime Deposits, Industrial Plants	3" - 10" (75 - 250mm)	125' x ¾"or 150' x 5/8" (38m x 19mm or 45m x 16mm)	114kg	200' (60m)	3⁄4HP


POWER DRAIN CLEANER COMPARISON CHART

GENERAL ELECTROMECHANICAL DRAIN CLEANERS

All the GENERAL Electromechanical Drain Cleaners use FLEXICORE WIRE ROPE CENTRE CABLES. Heavy gauge wire is coiled around 42-strand wire rope and heat treated. Cables are of high strength and correct flexibility. Electric machine cables are wound left hand.



Heavy gauge wire coiled tightly around a 42 strand aircraft type wire rope and heat treated. Has the correct strength and flexibility. 1/4" and 5/16" cables have basin plug ends and cables of 3/8" 10mm and larger can be fitted with cutters to their female connectors.



3" - 6" pipes

4" - 10" pipes



FLEXICORE CABLE SIZE	FOR USE IN FOLLOWING PIPE SIZI
1/4" Cable	11⁄4" – 2" pipes
5/16"Cable	1 ¹ /2" – 2" pipes
3⁄8" Cable	2" – 3" pipes
1/2" Cable	3" – 4" pipes (not roots)

5/8" Cable

3/4" Cable



Replacement Cables / Cables for Super-Vee, Power-Vee, Collet Chuck Handylectric and PH Drain Rooter:

Order		Dia. &	Length	Wt.
Code	Cable No	m x mm	ft x in	kg
with EL Basi	n Plug Head			
3193Y	25HE1	7.5 x 6	25 x ¹ /4	1.8
3194B	50HE1	15 x 6	50 x ¹ /4	4.1
3197K	25HE1-A	7.5 x 8	25 x 5⁄16	2.7
3198N	50HE1-A	15 x 8	50 x ⁵⁄16	5.5

with Female Connector

3194B	50HE1	15 x 6	50 x ¼	4
3197K	25HE1-A	7.5 x 8	25 x 5⁄16	2

3200A	25HE2	7.5 x 10	25 x 3⁄8	
3201D	35HE2	10.5 x 10	35 x 3⁄8	





The Small Drain Specialist.



speed trigger switch. Drum Cable maximum capacity- 35' x 3/8" or 50' x ⁵/16"; 10.5m x 10mm or 15m x 8mm.

Similar in specification to the Super-Vee with added features: Feeds cables forwards or back, by means of a feed lever. Drives 10mm 3/8" cables at 16'

SUPER-VEE

Order Code (Unit No/Volt. 50Hz)	Cables i m mm	in units ft in	Cable Ref	BoxedWt kg	
The following ur	nits include 2	2 cables and	the HECS	cutter set	
3009T	7.5 x 6	25 x ¼	25HE1	9	
SV-A/240	7.5 x 10	25 x 3⁄8	25HE2		
3011A	7.5 x 6	25 x ¼	25HE1	9	
SV-A/110	7.5 x 10	25 x ³ ⁄8	25HE2		
The following units do not include the HECS cutter set					
SV-F-240V	7.5 x 6	25 x ¼	25HE1	6	
SV-F-110V	7.5 x 6	25 x ¼	25HE1	6	

HECS Handylectric Cutter Set includes :

Order Code	Part No.	
3153E	AH	Arrow Head
3154H	FAH	Flexible Arrow
3159W	11/4SCB	11⁄4" 32mm Si
3155K	BG	Boring Gimlet
3156N	DHBG	Down Head E

w Head ide Cutter Blade t Boring Gimlet

Accessories and Parts for Super-Vee

Order Code	Part No.	
3035W-P	V	
3012D	PC	I
SV-25	SV-25	

Plastic Carrying Case Plastic Cartridge Cable Grippers

POWER-VEE

Order Code (Unit No/Volt. 50Hz)	Cables i m mm	in units ft in	Cable Ref	BoxedWt kg
The following uni	ts include 2	cables and th	e HECS cu	utter set
PV-A-240V	7.5 x 6	25 x ¹ /4	25HE1	10
	7.5 x 10	25 x 3⁄8	25HE2	
PV-A-110V	7.5 x 6	25 x ¼	25HE1	10
	7.5 x 10	25 x 3⁄8	25HE2	

Accessories and Parts for Power-Vee

Order	Part
Code	No.

3035W-PV PCC Plastic Carrying Case for Power-Vee










Backer

Backer Electric Company Limited, founded in 1938, is the market leader in the design and manufacture of heating elements, supplying products in high volume to the majority of household brandnames, producing domestic electrical appliances, spares to parts distributors and specialist elements for use in Industrial, Catering and Commercial applications.

Backer manufactures all products to the most stringent quality control procedures, meeting all of the relevant British and European standards.



09192L ELEMENT FOR WATER HEATERS, 3 KW




The BMST Thermostat is an ideal solution for retrofit to existing installations, thus bringing your old system up to the new standard by simply changing the thermostat.



For more information on any of these products, please email: enquiries@wgreerltd.co.uk

/4" Overflow Pipe, Pushfit and Universal Fittings



For more information on any of these products, please email: enquiries@wgreerltd.co.uk

Made in

1¹/4" and 1¹/2" Overflow Pipe and Pushfit Fittings



1 ¹ /4" Code	1 ½" Code	Standing Waste Back	
HDPE White Pip		with backn	g wastes are su ut and washers ength of stand p
HD1-3M	HD2-3M	When orde	ring state:
Pipe Clip		— (1) Code (2) Height i	required if not
	T30		m flange x 3 ¹ /
		Code	SWL
90° Bend			m flange x 3 ¹
		Code	TWI
S4A	T4A	1 ¹ / ₄ " x 70m	m flange x 1 ⁻¹
		Code	SWS
90° Knuckle Ber	nd	1 ¹ / ₂ " x 70m	m flange x 1 ¹
S4E	T4E	_ Code	TWS
90° Bend x BSP	coupling nut T5	Tank Overflow	roducts
S5	T5	Unslotted V	Vaste without (
	T5	Unslotted V 11/4" x 70m	Waste without (m flange x 3 ¹ /
Straight Connec	T5 ctor	Unslotted V Unslotted V 1 ¹ / ₄ " x 70m Code	Waste without (m flange x 3 ⁻¹ , W
S5	T5	Unslotted V Unslotted V 1 ¹ / ₄ " x 70m Code	Waste without (m flange x 3 ⁻¹ , W m flange x 3 ⁻¹ ,
Straight Connec	T5 ctor	Unslotted V Unslotted V 11/4" x 70m Code 11/2" x 70m Code	Waste without (m flange x 3 ¹ / W m flange x 3 ¹ / W
S5 Straight Connection S18	T5 ctor	Unslotted V Unslotted V 11/4" x 70m Code 11/2" x 70m Code	m flange x 3 ^{1/} W m flange x 3 ^{1/} W m flange x 3 ^{1/} W m flange x 1 ^{1/}
S5 Straight Connec 518	T5 ctor	Tank Overflow Pumbing P Unslotted V $1\frac{1}{4}$ x 70m Code $1\frac{1}{4}$ x 70m Code $1\frac{1}{4}$ x 70m Code $1\frac{1}{4}$ x 70m Code $1\frac{1}{4}$ x 70m	Waste without (m flange x 3 ¹ / W m flange x 3 ¹ / W2 m flange x 1 ¹ / W m flange x 1 ¹ /
S5 Straight Connec 518 Tee V8	T5 ctor T18	Image: Second system Unslotted V Image: Second system Image: Second system Image: Second system <td< td=""><td></td></td<>	
S5 Straight Connec S18 Tee	T5 ctor T18	Tank Overflow Pumbing P Unslotted V $1\frac{1}{4}$ x 70m Code $1\frac{1}{4}$ x 70m Code $1\frac{1}{4}$ x 70m Code $1\frac{1}{4}$ x 70m Code $1\frac{1}{4}$ x 70m	Waste without (m flange x 3 ¹ / W m flange x 3 ¹ / W2 m flange x 1 ¹ / W m flange x 1 ¹ /
S5 Straight Connec 518 Tee V8 Adaptor	T5 ctor T18 V1	Tank Overflow Pumbing P Unslotted V $1\frac{1}{4}$ x 70m Code $1\frac{1}{4}$ x 70m Code $1\frac{1}{4}$ x 70m Code $1\frac{1}{4}$ x 70m Code $1\frac{1}{4}$ x 70m	Waste without (m flange x 3 ¹ / W m flange x 3 ¹ / W2 m flange x 1 ¹ / W m flange x 1 ¹ /
S5 Straight Connec 518 Tee V8 Adaptor S7	T5 ctor T18 V1 T7	Tank Overflow Pumbing P Unslotted V $1\frac{1}{4}$ x 70m Code $1\frac{1}{4}$ x 70m Code $1\frac{1}{4}$ x 70m Code $1\frac{1}{4}$ x 70m Code $1\frac{1}{4}$ x 70m	Waste without (m flange x 3 ¹ / W m flange x 3 ¹ / W2 m flange x 1 ¹ / W m flange x 1 ¹ /
S5 Straight Connec S18 Tee V8 Adaptor	T5 ctor T18 V1 T7	Tank Overflow Pumbing P Unslotted V $1\frac{1}{4}$ x 70m Code $1\frac{1}{4}$ x 70m Code $1\frac{1}{4}$ x 70m Code $1\frac{1}{4}$ x 70m Code $1\frac{1}{4}$ x 70m	Waste without (m flange x 3 ¹ / W m flange x 3 ¹ / W2 m flange x 1 ¹ / W m flange x 1 ¹ /



For more information on any of these products, please email: enquiries@wgreerltd.co.uk

Τ9

S9

Water Storage Cistern Fittings (E x By e-law 30 Fittings)

H28





3/4"	1"	1 ¹ /4"	1 ¹ /2"	2"
Code	Code	Code	Code	Code
Complete Scro filter - standar		verflow Conn	ector with q	uick release

R40

R45

Complete Screened Tank Overflow Connector	with quick release
filter - extended model	

R30E - R40E R45E -					
	R30E	-	R40E	R45E	-

Screened Tank Breather

R30

R31 - SWLFBR TWLFBR ZWLFBR					
	R31	-	SWLFBR	TWLFBR	ZWLFBR



Screened Breather/Filter with compression joint to pipe

R32					
	R32	-	-	-	-



Tank Lid Adaptor for expansion pipe

R33	-	-	-	-
-----	---	---	---	---

2 Way Expansion Pipe Adaptor

R34

Tank Connector

R4M

H11M S11M T11M

Z11M





	27.11	4.11	4 17 11	4 17 H	2"	ר
	_{3/4} " Code	1" Code	1 ¼" Code	1 ¹ /2" Code	2" Code	
	Complete ³ /4" BL30-3/4					Fittinas)
	Screened Brea	ather/Filter/F	rost Cover w	ith compressi	ion joint to	aw 30
	-	-	SWLFCV	TWLFCV	-	Ve-
	In-Line Screer	ned/Filter Pip	e Coupling			(Ex B
	RWILF	HWILF	SWILF	TWILF	ZWILF	spi
	Frost Protecti Connect pipe	on Dip Tube I to provide le	Bend Ingth of dip tu	be required		Fittin
	-	-	S5	T5	Z5M	stern
	90° Multifit x	Plain End				Ue U
	-	-	MS4L	MT4L	MZ4L	Stora
	90° Multifit Be	end				Water
61	-	-	MS4	MT4	MZ4	



Tun Dishes and Non-Return Valves

Tun Dishes



Tun Dish with ³/₄" pushfit outlet

Code TUN-1



Tun Dish with 19/23mm universal outlet

TUN-2



One-Piece Side Inlet Tun Dish with 19/23mm universal outlet

	TUN-3
Chrome plated	TUN-3CP



Non-Return Valve with 19/23mm universal connections

Code

R28-NRV



One-Piece Tun Dish with 3/4" loose nut inlet x 19/23mm universal outlet

Chrome plated



90° Elbow with integral Non-Return Valve. Plain tail Inlet x 19/23mm universal outlet

Code

Code

R29-NRV

TUN-4CP In-Line Non-Return Valves



One-Piece Tun Dish with 19/23mm universal inlet x 1¹/₄" universal outlet

TUN-6

TUN-4

MAALPINE The Plumbers' First Choice



Convalve Non-Return Valve with 1 ¹/₄" universal connections to take pressure-relief discharge from pressurised hot water cylinders

CONVALVE-125



Convalve Non-Return Valve with 1 ¹/₄" plain tail x 1 ¹/₄" universal outlet to take pressure-relief discharge from pressurised hot water cylinders

Code CONVALVE-125P



Tun Dishes and Non-Return Valves

Non-Return Valves for WC Overflow

Code



Tunvalve (Clear) with 3/4" female threaded inlet connection to WC overflow outlet x 19/23mm universal outlet Code TUNVALVE



(Clear) with 19/23mm universal connections

Tunvalve Straight Through

TUN5-CL

WC Overflow Kits with Tun Dish and Tee Pieces

WC Overflow Kits with Tun Dish -Overflow into Flush Pipe

Before installation relaxation of Bye-law 84 is required by local water authority



WC Overflow Kit comprises TUN-2, V33T, 90° pushfit elbow and two 3/4" x 12" lengths of overflow pipe

Not suitable for use with high level cisterns

Code

TUNKIT-1

TUNKIT-3

WC Overflow Kit comprises TUN-3, V33T, 90° pushfit elbow and two 3/4" x 12" lengths of overflow pipe

Not suitable for use with high level cisterns



The Plumbers' First Choice

Tee Pieces



Tee Piece 1¹/₂" BSP nut x 1 ¹/₂" universal x 19/23mm universal connection

Not suitable for use with high level cisterns



Tee Piece with universal connection to flush pipe at both ends x 19/23mm universal connection

Not suitable for use with high level cisterns

T-FP



Tee Piece 1¹/₂" BSP nut x 1 ¹/₂" BSP thread x 19/23mm universal connection

Not suitable for use with high level cisterns

V33S-22



Code

VC Overflow Kits with Tun Dish and Tee

Pieces



Code TUNVALVE



Anti-Syphon Traps (Silentraps)



Resealing Bottle Traps


Made in Britain





For more information on any of these products, please email: enquiries@wgreerltd.co.uk

Bottle Traps with 75mm Water Seal



For more information on any of these products, please email: enquiries@wgreerltd.co.uk

Chrome Plated Basin Traps, Pipe and Wall Flange





1¹/₄" x 50mm Water Seal Brass Adjustable Inlet Cylindrical Bottle Trap with 12" length of 32mm OD CP brass waste pipe and wall flange

Code CA32MINI-CB



1¹/₄" x 50mm Water Seal Plastic Adjustable Inlet Tubular Trap with 12" length of 32mm OD CP brass waste pipe and wall flange

Code

TA32UK-CB



1¹/₄" x 50mm Water Seal Plastic Adjustable Inlet Tubular Anti-Syphon Trap (Silentrap) with 12" length of 32mm OD CP brass waste pipe and wall flange



1¹/₄" x 50mm Water Seal Brass Adjustable Inlet Square Bottle Trap with 12" length of 32mm OD CP brass waste pipe and wall flange

CA32SQUK-CB



1¹/₄" x 75mm Water Seal Brass Adjustable Inlet Cylindrical Bottle Trap with 16" length of 32mm OD CP brass waste pipe and wall flange

Code

CA32UK-CB



1¹/₄" x 75mm Water Seal Plastic Adjustable Inlet Bottle Trap with 16" length of 32mm OD CP brass waste pipe and wall flange



1¹/₄" x 75mm Water Seal Brass Adjustable Inlet Bottle Trap with 16" length of 32mm OD CP brass waste pipe and wall flange

A32UK-CB

A32UK-CP

- All kits except TA32UK-CB and TA32VUK-CB supplied with MS4-32SOLVENT fitting see pages 48 and 52
- For Chrome Plated Brass Waste Pipe and Fittings see page 52



Code



Tubular Traps with 75mm Water Seal

IP	1¼" 1½" 2" Code Code Code Swivel 'P' SA10 SC10 SE10	B	1¼" 1½" 2" Code Code Code Low Inlet
-	Anti-Syphon (Silentrap) SA10V SC10V SE10V	Ego	50mm Water Seal BT4
	Adjustable Inlet ASA10 ASC10 ASE10		Adjustable Inlet with connection for 19/23mm pipe ASA10-SP*ASC10-SP* -
	Adjustable Inlet Anti-Syphon (Silentrap) ASA10V ASC10V ASE10V	IJ	Swivel 'S' SB10 SD10 SF10
	Adjustable Inlet Basin Trap with centre pin waste	Is.	All One SP10 TP10 ZP10
. (ASA10W* Adjustable Inlet Sink Trap		All One Anti-Syphon (Silentrap) SP10V TP10V ZP10V
U	with centre pin waste - FST1WP* -		All One Basin Trap with centre pin waste SP10W* -

Made in Britain

All traps marked* available as anti-syphon (Silentrap). Add suffix 'V' to code. See page 4 for technical details

For more information on any of these products, please email: enquiries@wgreerltd.co.uk





Straight Through with one cleaning eye

1 ¹ / ₄ " Inlet x 1 ¹ / ₄ " outlet	X10 -	-
Straight Through Anti-Syphon (Silentrap)	with one cleaning eye	
1 ¹ / ₄ " Inlet x 1 ¹ / ₄ " outlet	X10V -	-
Straight Through with two cleaning eyes		
1 ¹ / ₄ " Inlet x 1 ¹ / ₄ " outlet	X10A -	-
1 ¹ / ₄ " Inlet x 1 ¹ / ₂ " outlet	Y10 -	-

All traps marked* available as an ti-syphon (Silentrap). Add suffix 'V' to code. See page 4 for technical details

Made in Britair

Domestic Appliance Traps 1 ¹/₂" x 75mm Water Seal

General

- Domestic Appliance Traps provide the facility to accept the discharge from a washing and/or dishwashing machine(s) and are suitable for new and existing installations
- In all cases a blank cap, plug or blank nozzle is provided with the trap. Should the domestic appliance not be connected at the time of installation, the trap will function as a normal sink trap whilst providing an easily accessible point for the future installation of any appliance(s)

Sink Traps with connection for the discharge from domestic appliance(s)







WM2V

WM12*

WM15*

Code

Code



Code WM2



WM11*




WM14*



Standpipe Trap and Fittings



Standpipe Cap with retaining clip





Twin Connector for plumbing two domestic appliance discharge hoses into standpipe trap

- Multifit outlet to suit either 1 ¹/₂" or 40mm diameter standpipe
- 135° swivel nozzles for washing and/or dishwashing machine discharge hoses supplied with blanking plugs
- Discharge hose(s) to be taken to the height stated by the appliance manufacturer(s)
- An air break, as specified by appliance manufacturers is incorporated within the connector

Code

Standpipe Trap

Code



WM3*



Code

Made in Britain



All traps marked* available as anti-syphon (Silentrap). Add suffix 'V' to code. See page 4 for technical details



Sink Trap with TeeVent

- The TeeVent system, which inc orporates a non-r eturn valve, provides an air br eak and enables the waste system to be sealed. This system has the adv antage over a standpipe arr angement in that should a block age occur, the non-r eturn valve prevents flooding
- TeeVent fittings may be used with domestic appliance tr ap WM4
- All domestic appliance tr aps must be fitted in acc ordance with the fixing instruction leaflet included with each tr ap

Code





Code

Code

- TV1 can be connected direct to the trap
- TV2 can be extended away from the trap by inserting a length of 1 1/2" waste pipe between Multifit connections of the TeeVent and the trap

Accessories

	Straight Nozzleforconnection to 1 ½" MultifitCodeWMF390° Nozzlefor connection		Swept Tee BSP nut x BSP thread x nozzle for discharge hose of domestic appliance
	to 1 ¹ / ₂ " Multifit	1 ¹ / ₂ " x 1 ¹ / ₂ " x ³ / ₄ "	Code V33L
		1 ¹ / ₄ " x 1 ¹ / ₄ " x ³ / ₄ "	Code V34L
	Code WMF4		Tee Piece BSP nut x BSP
	135° Nozzle for connection to 1" BSP thread	Start -	thread x 135° nozzle for discharge hose of domestic appliance
	Code MA15	11/ 1 1/ 3/	Cada V22C
	Planking Plug for trans and	1 ¹ / ₂ " x 1 ¹ / ₂ " x ³ / ₄ "	Code V33S
	Blanking Plug for traps and fittings	When installing domestic appliance traps, care should be taken to observe the instructions of the manufacturer of the appliance, particularly	
	Code 228532	with regard to the he	eight of the discharge hose n of an air break or vent to

Appliance Trap and Accessories

WM4*

All traps marked* available as anti-syphon (Silentrap). Add suffix 'V' to code. See page 4 for technical details

atmosphere






General

Space Saver Kits are designed to allow full use of stor age space below the sink bowl(s) and are suitable for use with almost all British and Eur opean sink s


All kits ha ve $1\frac{1}{2}$ " inlet connections and the pr ovision for the dischar ge hose(s) of domestic appliance(s). Also supplied with an $1\frac{1}{2}$ " x 75mm w ater seal tubular swiv el 'P' trap

Each kit is boxed individually and supplied with an illustr ative drawing



Single Bowl Kit

Code SSK1



Double Bowl Kit

Code




Three Bowl Kit

Code





SSK2



Plumbing Kit for adjustable height basin or sink

Code

FLEXKIT1



For more information on any of these products, please email: enquiries@wgreerltd.co.uk


Kit for Adjustable Height Basin or Sink



General

- Standard Kits have the provision for the discharge hose(s) of domestic appliance(s) and are suitable for use with almost all British and European sinks
- All kits have 1¹/₂" inlet connections and the provision for the discharge hose(s) of domestic appliance(s). Also supplied with an 1¹/₂" x 75mm water seal tubular swivel 'P' trap
- Each kit is supplied in a polythene bag complete with an illustrative drawing


Code



SK1

Bowl and a Half Kit

Code



SK1A

Bowl and a Half Kit



Double Bowl Kit

Code	SK2
------	-----



Made in Condensate Products for Connecting Condensate Discharge

Basin and Sink Traps





pipe. Supplied with blanking cap Code ASA10-SP* 1¹/₂" x 75mm Water Seal Tubular Swivel Sink Trap

1¹/₄" x 75mm Water Seal Tubular Swivel Basin Trap

with adjustable inlet and

connection for 19/23mm

with adjustable inlet and connection for 19/23mm pipe. Supplied with blanking cap

Code ASC10-SP*

1¹/₂" x 75mm Water Seal Tubular Swivel Sink Trap with adjustable inlet, nozzle for discharge hose of domestic appliance and connection for 19/23mm

pipe. Supplied with blanking cap

Code ASC10-CO*

19/23mm Inlet and Outlet x 75mm Water

Seal Offset Trap to receive discharge from condensing boiler. Supplied with support clip

Code OBT1-CO



34mm Open Inlet x 75mm Water Seal Offset Trap x 19/23mm Outlet to accept flexible pipe from condensing boiler. Supplied with support clip

Code OBT2-CO

All traps marked* available as anti-syphon (Silentrap). Add suffix 'V' to code. See page 4 for technical details Flexible Connector from Condensing Boiler to Rigid or Flexible Condensate Discharge Pipe

- Easy connection to boiler condensate discharge pipe
- Allows for disconnection in freezing conditions for discharge to be redirected into a receptacle
- Universal connections suitable for 19/23mm rigid pipe and 25mm flexible pipe



Flexible Condensate Pipe Kit

- For use in installation of condensing boilers
- Eliminates use of traditional rigid discharge pipe and fittings thereby allowing complete flexibility to discharge point
- Includes fittings to allow for easy connection to sanitary pipework
- Allows for disconnection in freezing conditions for discharge to be redirected into a receptacle
- Particularly useful where installation space is restricted



Flexible Condensate Pipe Kit - contents

- 1 x 3m length of 25mm flexible pipe
- 6 x 25mm pipe clips

Code

- 2 x Straight connectors with universal connections suitable for 19/23mm rigid pipe and 25mm flexible pipe
- $1 \times 1 \frac{1}{2}$ " plain tail ABS solvent weld reducer to 19/23mm rigid pipe and 25mm flexible pipe

CONFLEX-KIT1

For more information on any of these products, please email: enquiries@wgreerltd.co.uk

Condensate Products





from Condensing Boiler to Sanitary Pipework



Soakaway - Container for use with limestone chippings. External use only



110mm x 300mm x 1 $\frac{1}{4}$ /1 $\frac{1}{2}$ Pipe top and side Inlet **Connections** to receive discharge from condensing boiler. 19/23mm x 32mm solvent weld fitting provided to increase size of discharge pipe before it passes through the external wall Code

SOAK1GR

CLAMP1GR

CLAMP1WH

V1MX-CO

Auxiliary Fittings



Pipe Clamp to suit 1 $\frac{1}{4}$ "/1 $\frac{1}{2}$ " Pipe to BS EN 1451-1:2000 /BS EN 1329-1:2000 with universal connection for 19/23mm rigid pipe and 25mm flexible pipe



1¹/₂" x 1 ¹/₂" x 19/23mm Universal Slip Tee with universal connection for 19/23mm rigid pipe and 25mm flexible pipe

Code

Code (Grey)

Code (White)



In-line Vertical Non-Return Valve with inlet and outlet connection for 19/23mm pipe



CONVALVE Code Straight Connector with universal connections for 19/23mm rigid pipe and

25mm flexible pipe R1M-CO



Code

50mm Tun Dish with 19/23mm pipe outlet

```
TUN-2
```

Mechanical Soil Pipe Boss Connectors



















Mechanical Soil Pipe Boss Connector 57mm hole saw size. Supplied with fixing tool 4"/110mm x 1 ¹/₄" pipe **BOSSCONN110-BL** Code 4"/110mm x 1 ¹/₂" pipe Code **BOSSCONN110T-BL** 4"/110mm x 1 ¹/₄" pipe Code BOSSCONN110-GR 4"/110mm x 1 ¹/₂" pipe BOSSCONN110T-GR Code

Two-Piece Cast Iron Soil Pipe Boss Connector to suit 22mm drill size. Supplied with fixing tool 4"/110mm x 1 ¹/₄" pipe Code **BOSS110C AST-BL** 4"/110mm x 1 ¹/₂" pipe **BOSS110T CAST-BL** Code 3¹/₂"/90mm x 1 ¹/₄" pipe Code **BOSS90CAST-BL** 3¹/₂"/90mm x 1¹/₂" pipe Code BOSS90T CAST-BL 3"/82mm x 1 ¹/₄" pipe Code BOSS82CAST-BL 3"/82mm x 1 ¹/₂" pipe BOSS82TCAST-BL Code


Mechanical Soil and **Rainwater Pipe Boss** Connector for $1\frac{1}{4}$ pipe Code BOSSCONNI 258 I

Code	BUSSCONNT.25B L
Code	BOSSCONN1.25GR

Reducer in ABS 1¹/₄" plain tail

x 19/23mm univ ersal





connection

Rainwater Pipe Boss Connector for 19/23mm pipe Code **BOSSCONN-22MM**



R16-BL

R16-GR

Made in Bath Traps 75mm, 60mm, 50mm and 19mm Water Seal

Bath Traps without Overflows



Bath Traps with Ov erflows

Exporting Company Ltd




 $1\frac{1}{2}$ " x 75mm Water Seal with flexible overflow tube and CP overflow grating



 $1\frac{1}{2}$ " x 75mm Water Seal Anti-Syphon (Silentrap) with flexible overflow tube and CP overflow grating



1¹/₂" x 75mm Water Seal with flexible overflow tube and CP overflow grating and 70mm flange centre pin waste outlet fitting Code FJ10WC*



1¹/₂" x 60mm Water Seal

(Extended Body) with flexible overflow tube and CP overflow grating





1¹/₂" x 50mm Water Seal with flexible overflow tube and CP overflow grating



1¹/₂" x 50mm Water Seal Anti-Syphon (Silentrap) with flexible overflow tube and CP overflow grating

Code	FSK10E*	Code	FSK10	Code	FSK10V



All traps marked* available as anti-syphon (Silentrap). Add suffix 'V' to code. See page 4 for technical details





Bath Fillers with Trap and Overflow

General


Filler manufactured in cast brass

- Compact filler design 70mm diameter x 25mm deep suitable for curved baths
- Will fit overflow hole size 46mm to 65mm
- 0.5 bar pressure produces 33 litres per minute
 1.0 bar pressure produces 44 litres per minute
 2.0 bar pressure produces 57 litres per minute
- 650mm WRAS approved braided hose with 90° bend
- All traps 1 ¹/₂" x 50mm water seal with Multifit outlet
- Compression overflow connection to trap

- HC2650UK-FIL has a standard overflow length of 575mm but is available with a 1m length. Incorporates a swivel bath trap and CP brass waste with top access spring-loaded mushroom plug. Overall height 109mm
- HCN3365UK has a standard overflow length of 575mm but is available with a 1m length. Incorporates a CP brass waste and springloaded mushroom plug
- HCN3165UK has a standard cable and overflow length of 575mm but is available with a 1m cable and overflow. Incorporates CP brass waste and mushroom pop-up plug



Overflow Manifold (Wasteflow)



General

- Bath Wasteflow units enable the overflow and/or warning pipe from a cold water storage cistern and a WC flushing cistern (not fitted with an integral overflow) to be installed so that the discharge is directed into the bath via the bath overflow grating
- The construction of the Wasteflow is such that whilst acting as a conventional overflow for the bath, any overflow from a connected cistern is discharged through the overflow grating into the bath thereby providing a visible warning
- A feature of the Wasteflow design ensures that should the overflow grating be blocked, the overflow from the cistern is diverted to discharge directly into the bath trap and not

back along the overflow pipe thereby reducing the risk of flooding

Wasteflow is also available with connection for condensate or condense drain

Advantages

- Wasteflow is available in various forms that allow greater flexibility for the discharge of cistern overflows, condensate and condense
- No unsightly external overflow pipes
- No damage to outside walls
- No risk of freezing
- No risk to other tenants or public

Installation

- Wasteflow is supplied with a choice of 50mm, 60mm or 75mm water seal trap
- Wasteflow is installed under the roll of the bath
- Wasteflow fittings shown on page 20 enable a range of connections that may be housed within the roll of the bath or if necessary extended into a duct space
- Overflow pipes connected to Wasteflow should have an adequate and continuous fall to ensure a natural gravity discharge


Wasteflow with pop-up waste and trap: CP brass control knob: CP stainless steel waste flange and plug

With L10 Trap	PUWF3-CP*
With SM10E Trap	PUWF2-CP*



Wasteflow with trap

With FJ10 Trap	FJWF1*		
With FSK10 Trap	FSKWF1*		
Without Trap	WF1		
Bath Waste Outlet Fittings see page 83			



Wasteflow with 1 $\frac{1}{2}$ " waste outlet fitting, plug, chain and two way connector

Code

WF21

Wasteflow Manifolds have a 1 V₂" BSP male thread on the inlet and will normally require an additional fitting from the list on page 20

All traps marked* available as anti-syphon (Silentrap). Add suffix 'V' to code. See page 4 for technical details

Made in Britain

Overflow Manifold (Wasteflow) Chrome Plated Bath Trap with Overflow

Wasteflow



Wasteflow can be fitted with R11, R12 or R15 connector (order as required) for connection to overflow warning pipe. Side inlet connection for 19/23mm condensate or condense drain

WF21-SP

Wasteflow Fittings

	J		
Ø	Straight Connect x connection for	or 1 ¹ / ₂ " loose nut 19/23mm pipe	
	Code	R11	
-0	Four Way Connect nut x four connect pipe, supplied wi	ctions for 19mm	
~	Code	R12	
	ABS Adaptor to convert 19mm connections on R12 and R15 fittings up to 23mm OD pipe		
	Code	R13	
	³ / ₄ " In-Line Non-R	leturn Valve	
	Code	R14	
Ø	two connections supplied with on	e plug	
	Code	R15	

See page 63 for WC Overflow Kits with Tun Dish

Chrome Plated Brass Bath Traps with Combined Waste and Overflow



 $1\frac{1}{2}$ " x 50mm Water Seal CP Brass Trap : $1\frac{1}{2}$ " CP brass combined waste and overflow with 70mm spring-loaded mushroom plug and matching overflow face

Code BRASSTRAP-50-CP

 $1\frac{1}{2}$ " x 25mm Water Seal CP Brass Trap : $1\frac{1}{2}$ " CP brass combined waste and overflow with 70mm spring-loaded mushroom plug and matching overflow face

Code BRASSTRAP-25-CP

Code

110mm x 50mm Water Seal Pushfit Traps, Urinal **Bowl Syphonic Traps and Condensation Trap**

110mm x 50mm Water Seal Pushfit Traps

Pushfit Traps are manufactured in high density polyethylene and the inlet and outlet sealing rings from a proven synthetic rubber compound. Pushfit traps will suit WC squatting pans, slop hoppers or similar appliances with 90-114mm plain end outlet and will connect to 110mm pipe



Code

WCTRAP4P

WCTRAP4S



Code

Urinal Bowl Syphonic Traps

Syphonic Traps have inlets to suit continental style syphonic urinal bowl to create a 75mm water seal trap. Outlet to suit 2" BS EN 1329-1:2000 solvent weld pipe



Syphonic 'P' Trap

Code



Syphonic 'S' Trap

Code

M'ALPINE

Condensation Trap

Condensation Trap has been designed as a straight socket connector for 110mm and 125mm pipe (commonly used as ducting for basic air extraction systems) and provides an internal trap/diverter which will collect condensation forming on the internal surface of the extract pipework. It allows for the connection of a 19/23mm pipe, which can be installed to drain off the condensation to a convenient position



110mm pipe Code

125mm pipe Code CONTRAP2



nic 'P' Trap HCUP50UK HCUP50UK HCUP50UK HCUS50UK HCUS50UK HCUS50UK HCUS50UK HCUS50UK HCUS50UK HCUS50UK The Plumbers' First Choice Omm and as ducting for d provides an collect ternal surface 's for the which can be hation to a hpipe CONTRAP1

Made in 90mm Shower Traps with 50mm Water Seal

90mm Shower Traps with 50mm Water Seal and removable 113mm Flange to

CP Plastic Flange **CP Brass Flange CP** Brass Flange 90mm x 50mm Water Seal with 1 ¹/₂" Multifit Outlet Overall height 70mm ST90CP10-70 ST90CB10-70 ST90CPB-P-70 90mm x 50mm Water Seal with 1 ¹/₂" Multifit Outlet Overall height 82mm ST90CP10 ST90CB10 ST90CPB-P 90mm x 50mm Water Seal with 1 1/2" Multifit Outlet High-flow high-performance trap. Over all height 85mm -ST90CP10-HP2 ST90CB10-HP2 ST90CPB-P-HP2 90mm x 50mm Water Seal with 2" Multifit Outlet High-flow high-performance trap. Over all height 85mm ST90CP10-HP ST90CB10-HP ST90CPB-P-HP 90mm x 50mm Water Seal with 2" Universal Vertical Outlet Overall height 108mm

ST90CP10-V

ST90CB10-V

ST90CPB-P-V

90mm Shower Traps with 50mm Water Sea



facilitate easy cleaning





ST90CPB-S



ST90WH10

90mm x 50mm Water Seal with 1 $\frac{1}{2}$ " Multifit Outlet High-flow high-performance trap. Over all height 85mm



ST90CPB-S-HP2



ST90WH10-HP2

90mm x 50mm Water Seal with 2" Multifit Outlet High-flow high-performance trap. Over all height 85mm



ST90CPB-S-HP



ST90WH10-HP

90mm x 50mm Water Seal with 2" Universal Vertical Outlet Overall height 108mm







ST90WH10-V

Do not pour drain cleaner down these products



For more information on any of these products, please email: enquiries@wgreerltd.co.uk





1¹/2" Shower Traps with Top Access

Traps with Standard Waste and Flange

- Waste grid and dip tube removable from top to facilitate easy cleaning
- 1¹/₂" Multifit outlet
- 70mm or 85mm standard waste and flange - white plastic, CP plastic or CP brass
- Gold plated wastes and grids only supplied as separate items - see page 27

19mm Water Seal Trap

Overall height 95mm

85mm White **Plastic Flange**

STW5-R

STW1-R





STW2-95

STW6-95

50mm Water Seal Resealing Trap Overall height 118mm



STW2-R



STW6-R

80mm Water Seal Resealing Trap Overall height 154mm



STW9-R



STW11-R


MALPINE













STW12-R

STW10-R

STW10-RB



STW12-RB

1 1/2" Shower Traps with Top Access

Traps with Waste and Mushroom Flange

- Mushroom flange and dip tube removable from top to facilitate easy cleaning
- 1¹/₂" Multifit outlet

70mm or 85mm mushroom flange available in white plastic or CP stainless steel complete with standard locking nut

70mm White Plastic Mushroom Flange	85mm White Plastic Mushroom Flange	70mm CP Stainless Steel Mushroom Flange	85mm CP Stainless Steel Mushroom Flange
19mm Water Seal Trap	Overall height 95mm		
STW1-M	STW5-M	STW3-M	STW7-M
50mm Water Seal Trap	Overall height 95mm		
			900
STW2M-95	STW6M-95	STW4M-95	STW8M-95
50mm Water Seal Resea	aling Trap Overall height 1	18mm	
STW2-M	STW6-M	STW4-M	STW8-M
STW2-M 80mm Water Seal Reserved	STW6-M	STW4-M	STW8-M
	STW6-M	STW4-M	STW8-M



70mm Shower Trap and Shower Trap Accessories



70mm x 25mm Water Seal Trap with Top Access: 85mm CP Stainless Steel Mushroom Flange with 1 ¹/₂" BS EN 1329-1:2000 solvent weld outlet. Overall height 50mm

Code

ST70SS85

Only suitable for shower trays with a 70mm waste outlet

Standard Waste with grid to suit tray with maximum thickness of 22mm

White Plastic	CP Plastic	CP Brass	GP Plastic	
STW70WH	STW70CP	STW70CPB	STW70GP	
STW85WH	STW85CP	STW85CPB	STW85GP	•
Long Waste with gr with maximum thic	•	Grid only	AA*ALPINE Plumbing Products	The Plumbers' First Choice
White Plastic	CP Plastic	White Plastic	CP Plastic	GP Plastic
STW70WHL	STW70CPL	STWGR-WH	STWGR-CP	STWGR-GP
STW85WHL	STW85CPL			
Standard Locking N		Mushroom Flange		

Standard Locking Nut to suit tray with maximum thickness of 22mm



STW85LN

STW70LN

Long Locking Nut to suit tray with maximum thickness of 29mm

STW70LN L STW85LN L




Mushroom Flange



70mm Shower Trap and Shower Trap Accessories



Trap Washers, Bath and Shower Trap Accessories Exporting Company Ltd





Multifit Waste Fittings

Multifit Waste Fittings

	1 ¹ / ₄ "	1 ¹ / ₂ "	2"		1 ¹ / ₄ "	1 ¹ / ₂ "	2"
	Code	Code	Code		Code	Code	Code
YA	90° Bend				Straight Connector Multifit x European pipe size		
					x 32mm	•	x 50mm
	MS4	MT4	MZ4		S28L-ISO	T28L-ISO	Z28L-IS
7	90° Bend N pipe size	/ultifit x Eu	uropean		x 40mm	-	-
	x 32mm	x 40mm	x 50mm		ST28L-ISO	-	-
	MS4-ISO	MT4-ISO	MZ4-ISO		Adjustable	Straight Co	nnector
	10154-150	1014-130	10124-130	-7	Aujustable	Straight Co	meetor
\sim	90° Bend M European p)		
	pushfit	npe size m	ig scal		MS18E	M T18E	M Z18
	MS4-32MM						
	10134-3210110	-	-		Straight Co	nnector M	ultifit v
C	90° Bend A	BS solvent	t weld x		plain end*		
	32mm Euro						
	seal pushfit		5		MS18L	MT18L	
	MS4-32SOL		_			IVIIIOL	-
	90° Bend M	1ultifit x pla	ain end*		Swept Tee		
-7-7				Veralle			
	MS4L	MT4L	MZ4L		V8M	V1M	V15M
	135° Bend				11/2" Found	Slip Tee w	ith
						onnections	
	MS20	MT20	MZ20				,
					-	V1MX	-
	135° Bend	Multifit x p	lain end*		Reducer fo	r Fittings *	
	MS20L	MT20L	MZ20L		1 ¹ / ₂ " x 1 ¹ / ₄ "	T12M	-
					2" x 1 ¹ / ₄ "	-	ZS26
7	Straight Co	nnector			2" x 1 ½"	-	ZT26
		T28M	Z28M				
					2" x 19/23n	nm -	TUN-2
60.0	Straight Co	inector I	'4 X I '2				
		CTOOLA					
	-	ST28M	-				

Fittings marked * have plain ends which are designed to fit into other fittings or traps with Multifit or universal connection



	$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	$\begin{array}{cccc} 1^{1}/_{4}^{"} & 1^{1}/_{2}^{"} & 2^{"} \\ Code & Code & Code \end{array}$
	Reducer in ABS * 1 ¹ / ₄ " plain tail to BS EN 1329-1:2000 x 19/23mm universal connection	Straight Connector BSP male thread x Multifit
		S31M T31M -
		Multifit Tank Connector
	Reducer in ABS * 1 ¹ / ₂ " plain tail to BS EN 1329-1:2000 x 19/23mm universal connection	S11M T11M Z11M
	- R17 -	Multifit Bent Tank Connector
		MS4-TANK MT4-TANK MZ4-TANK
600	Rubber Reducer 1 ¹ / ₄ " x 1"/28mm	Blanking Cap for Multifit fittings
	T12R	S23M T23M Z23M
600	Straight Connector Multifit x BSP female thread	Blanking Cap for waste pipe wit universal connection
	S29 T29 Z29	S23U T23U Z23U
105	Straight Connector Multifit x BSP coupling nut	2" Caulking Ferrule
	S29-LN T29-LN -	S21A T21A Z21A
C	90° Bend Multifit x BSP coupling nut	In-Line Connector with Filter - Top Access universal connection x ABS plain spigot BS EN 1329-1:2000
	S5M T5M Z5M	- T28M-FIL -
	95° Bend Multifit x BSP coupling	Loose Nut
0	nut	S8M T8M Z8M
	S5M-A T5M-A -	
	135° Bend Multifit x BSP coupling nut	
	- ST90-OUT -	

Multifit Waste Fittings



Flexible Waste Fittings and Non-Return Valves

Flexible Connector offers maximum flexibility when conventional fittings cannot be used

- Maximum effective length 18"
- Plain spigot to suit Multifit and universal outlet traps or waste fittings
- Universal outlet connection

Non-Return Valves

1¹/₄"

_



Code Code Code In-Line Non-Return Valve with $1\frac{1}{2}$ " universal connections and

1¹/₂"

T28M-NRV



In-Line Non-Return Valve with 2" universal connections and top access for cleaning

Z28M-NRV

2"

E		
1 ¹ /4"	1 ¹ / ₂ "	2"
Code	Code	Code
FLEXCON1	FLEXCON2	-

Flexible Fittings

These fittings offer complete flexibility for any required angle or offset



Universal Connection x PVC Plain Spigot suitable for solvent welding to pipe BS EN 1329-1:2000

FLEXCON5 **FLEXCON6** FLEXCON8



In-Line Non-Return Valve with 2" BS EN 1329-1:2000 solvent weld connections and top access for cleaning

Z28M-NRVS

Non-Return Valves are designed to prevent a back flow of water. They must only be used when there is no alternative and on the basis that they are cleaned regularly

_



The Plumbers' First Choice



Sundry Fittings

S22L

T22L

-

Sundry Fittings

		1 ¹ / ₄ "	1 ¹ /2"	2"			1 ¹ /4"	1 ¹ / ₂ "	
	Code	Code	Code			Code	Code		
		90° Bend w	ith BSP ma	le thread		BSP Coupling			
		x BSP coupli				1" length	S12A-1	T12A-1	
		•	5			2" length	S12A-2	T12A-2	
		S1	T1	Z1		3" length	S12A-3	T12A-3	
		BSP Nut ord	dinary			BSP Coupling flush spigot			
		S8A T8A Z8A				European to UK waste adaptor			
		BSP Nut con S8B	T8B	Z8B			S12A-F	T12A-F	
			100	200		BSP Couplin	ng		
		Compression	n Ring for li	mperial					
		Copper				1 ¹ / ₄ " x 1"	S12C	-	
			T13			1" x ³ /4"	S12D	-	
				1220		BSP Coupli	ng waste o	utlet	
		BSP Couplin 1:2000 ABS	-		reducer				
	6-0	solvent weld							
						1 ¹ / ₂ " x 1 ¹ / ₄ "	-	T12	
		S25	T25	-		BSP Coupli	ng		
		Trap Inlet Re	educer			1 ³ / ₄ " x 1 ¹ / ₂ "	-	T12B	
						2" x 1 ½"	-	T12C	
		1 ¹ / ₄ " x 1"				2" x 1 ¼"	-	T12D	
		S16 1 ¹ / ₂ " x 1 ¹ / ₄ "	- T16	-		1 ¹ / ₂ " x 1"	-	T12H	
			110			BSP Coupli	ng		
	Blank Cap v	vith nut for	BSP			5			
		threads				1 ¹ / ₂ " x 2"	-	T12E	
		S23	T23	Z23		1 ¹ / ₂ " x 1 ³ / ₄ "	-	T12F	
		7" Extensior		octivo					
		length 5". A			MCALPINE The P	lumbers' First Cho	bice		
		shorter on a		. yer er	Fiumbing Products				

BSP Female x BSP Male Couplings

Sundry Fittings



Chrome Plated Brass Waste Pipe and Fittings

			32mm Code	35mm Code		42mm Code	
		-)	1m length of CP Brass Pip European pipe size PIPE32-1000-CB	e 1 ¼" UK pipe PIPE35-1000-		1 ¹ / ₂ " UK pipe size PIPE42-1000-CB	
		•	CP Pipe Clip				
			S32-CP	S35-CP		T42-CP	
gs			90° Compression Bend				
Li D			32A-CB 35A-CB		42A-CB		
Fitting	Į		135° Compression Bend				
and			-	35B-CB		42B-CB	
			Compression Tee				
Pipe			-	-		42E-CB	
			Compression Straight Cor				
Waste			32G-CB	35G-CB		42G-CB	
	6		Wall Flange				
a S S			WALLFLANGE-CP32	WALLFLANGE	-CP35	WALLFLANGE-CP42	
Bras			Synthetic Rubber Seal Reducers for above fittings				
				R/SEAL-35X	32	R/SEAL-42X32 R/SEAL-42X35	
Plated			ABS Solvent Weld Adaptor plastic solvent weld waste		ve fittings	to BS EN 1329-1:2000	
		/	ABSCON-32X1.25	ABSCON-35X1	.25	ABSCON-42X1.5	
Chrome			nd 32/35mm compression ss x 1 ¹ / ₄ " ABS solvent weld			32mm European pipe seal pushfit x 1 ^{1/} 4"	
5		Code	ABS32/35A-CB		Code	MS4-32MM	
52		compr	nt Connector 32/35mm ression CP br ass x 1 ¹ /4" Ilvent weld		size ring	d 32mm Eur opean pipe seal pushfit x 1 ¹ ⁄4" ent weld	
		Code	ABS32/35G-CB itable for use with 35mm and		Code	MS4-32SOLVENT	

For Multifit fittings suitable for use with 35mm and 42mm external diameter pipe see pages 48 and 49

For Chrome Plated Traps see pages 6, 7 and 20

Surefit Waste System

	1 ¹ / ₄ " Code	1 ½" Code	2" Code		11⁄4" Code
				1012	
V	HDPE Whit	te Pipe 3m	lengths		Swept Tee V8L
	HD1-3M	HD2-3M	HD3-3M		
	Pipe Clip				Swept Tee
y	530	T30	Z30	54	$\frac{11}{2} \times 11_{2} \times 11_{4} - \frac{11}{2} \times 11_{4}$
	90° Bend				Swept Tee Surefit x 19mm pushfit branch
	S4L	T4L	Z4L	6.5	1 ¹ / ₂ " x 1 ¹ / ₂ " x ³ / ₄ " -
					1 ¹ / ₄ " x 1 ¹ / ₄ " x ³ / ₄ " V24L
	135° Bend 	T20L			Swept Tee BSP nut x BSP th x nozzle for discharge hose domestic appliance
					$\frac{11}{12} \times 12^{1} \times 34^{1} - \frac{11}{2} \times 12^{1} \times 34^{1} - \frac{11}{2} \times 34^{1} - \frac{11}$
	Straight Co	onnector			1 ¹ / ₄ " x 1 ¹ / ₄ " x ³ / ₄ " V34L
	S18L	T18L	Z18L		Tee Piece BSP nut x BSP thr
	Church the Ca		1	Sar.	135° nozzle for discharge he of domestic appliance
	Surefit	onnector N	iuitint x		$1^{1/2} \times 1^{1/2} \times 3^{3/4}$
	S28L	T28L	Z28L		1 ¹ / ₄ " 1 ¹ / ₂ "
	De deservati	1/ 11 + - 1 1/ 11			Code Code Co
	Reducer 1 ¹	¹ / ₂ to 1 ¹ / ₄			90° Connector to soil pipe
	-	T12L	_		BS EN 1451-1:2000 size*
		1126			
	Blank Cap				S4M T4M
	Blank Cap	without nu	ut		135° Connector to soil pipe
0	Blank Cap		ıt Z23L		
0		without nu T23L			135° Connector to soil pipe BS EN 1451-1:2000 size*
	S23L Reducer fo	without nu T23L or Fittings	Z23L		135° Connector to soil pipe BS EN 1451-1:2000 size* S20M T20M
	S23L Reducer fo 2"-1 ¹ /4"	without nu T23L or Fittings $1^{1}/_{2}$ "- $1^{1}/_{4}$ "	Z23L 2"-1 ½"		135° Connector to soil pipe BS EN 1451-1:2000 size* S20M T20M Straight Connector to soil p
	S23L Reducer fo	without nu T23L or Fittings	Z23L		135° Connector to soil pipeBS EN 1451-1:2000 size*S20MStraight Connector to soil pboss BS EN 1451-1:2000 size

*BS 5254 size - if connecting to boss size BS 5255 add 5255 to code e.g. S4M 5255

S17

T17

Surefit waste fittings only suitable for M ^CAlpine HDPE waste pipe



Surefit Waste System

AN'ALPINE The Plumbers' First Choice Drain Connectors and Blanking O ff Caps

- Manufactured in polypropylene
- Finned seal spigot for internal connection to cast iron, plastic or clay 4"/110mm pipe



4"/110mm x 4"/110mm Connectorwith 'O'seal socket to fit 4"/110mm pipe to BS 4514Code (Black)DC1-BLCode (Grey)DC1-GRWith 14mm offsetCode (Black)DC1BL-OSCode (Grey)DC1GR-OS

Drain Connector with Boss



4"/110mm x 4"/110mm Connector with 'O' seal socket to fit 4"/110mm pipe to BS 4514 and $1\frac{1}{2}$ " universal pipe boss including

blanking cap Code (Black) DC1-BL-BO Code (Grey) DC1-GR-BO

Drain Connector 90° Bend



90° Bend 4"/110mm x 4"/110mm with 'O' seal socket to fit 4"/110mm pipe to BS 4514

Code (Black)	DC90-BL
Code (Grey)	DC90-GR

- Ideal for low level connections
- Reducers allow for connection to BS EN 1451-1:2000 and BS EN 1329-1:2000 pipe



4"/110mm Reducer Connector with sealing ring to fit to plastic waste pipe

	Code
$1^{1/4}$ " and $1^{1/2}$ "	DC2-BL
2"	DC3-BL



4"/110mm Reducer Connector with offset sealing ring to fit to plastic waste pipe $1\frac{1}{4}$ " and $1\frac{1}{2}$ " DC2BL-OS 2" DC3BL-OS



4"/110mm Blanking Cap suitable for sealing cast iron, plastic or clay 4"/110mm pipe

Code

DC4-BL

Temporary Blanking Off Caps

	Synthetic Rubber Cap for sealing 110mm pipe					
	Code		CAP100			
0	1 ¹ / ₄ " Code Synthetic pipe	1 ¹ / ₂ " Code Rubber Cap	2" Code for waste			
	S23MR	T23MR	Z23MR			



Mechanical Soil P ipe Boss Connectors

- Suitable for waste water and condensate discharge
- Simple dry fixing mechanical connection

Mechanical Soil Pipe Boss Connectors to suit 57mm hole saw size



- Universal connection for pushfit or solvent weld waste pipe
- All boss connectors supplied with fixing tool

Two-Piece Cast Iron Soil Pipe Boss Connector to suit 22mm drill size for CONDENSATE DISCHARGE ONLY



 $3\frac{1}{2}"/90 \text{ mm x 1 } \frac{1}{4}" \text{ pipe}$ Code BOSS90CAST-BL $3\frac{1}{2}"/90 \text{ mm x 1 } \frac{1}{2}" \text{ pipe}$ Code BOSS90TCAST-BL

3"/82mm x 1 ¹/₄" pipe Code BOSS82CAST-BL 3"/82mm x 1 ¹/₂" pipe Code BOSS82TCAST-BL



4"/110mm x 1 ¹/₄" pipe Code BOSSCONN110-BL 4"/110mm x 1 ¹/₂" pipe BOSSCONN110T-BL Code 4"/110mm x 2" pipe BOSSCONN110Z-BL Code 3"/82mm x 1 ¹/₄" pipe **BOSSCONN82-BL** Code 3"/82mm x 1 ¹/₂" pipe Code **BOSSCONN82T-BL** 3"/82mm x 2" pipe BOSSCONN82Z-BL Code



4"/110mm x 1 ¹/₄" pipe BOSSCONN110-GR Code 4"/110mm x 1 ¹/₂" pipe Code BOSSCONN110T-GR 4"/110mm x 2" pipe Code BOSSCONN110Z-GR 3"/82mm x 1 ¹/₄" pipe **BOSSCONN82-GR** Code 3"/82mm x 1 ¹/₂" pipe Code BOSSCONN82T-GR 3"/82mm x 2" pipe Code BOSSCONN82Z-GR

Mechanical Soil and Rainwater Pipe Boss Connectors



Mechanical Soil and Rainwater Pipe Boss Connector for 1¹/₄" pipe

	Code	BOSSCONN1.25BL
	Code	BOSSCONN1.25GR



Reducer in ABS1¼" plain tail x19/23mm universal connectionCodeR16-BLCodeR16-GR



Mechanical Soil and Rainwater PipeBoss Connector for 19/23mm pipeCodeBOSSCONN-22MM

Threaded Boss Connectors



Straight Connector2" BSP malethread x Multifit2" BSP x 1 1/4" MultifitZS31M

2" BSP x 1 ¹ / ₄ " Multifit	ZS31M
2" BSP x 1 ¹ / ₂ " Multifit	ZT31M
2" BSP x 2" Multifit	Z31M



Aluminium R oof Flashing (MacFlash)

General

- MacFlash Aluminium Roof Flashing offers an alternative to traditional lead roof slates
- The aluminium flashing is manufactured from high grade aluminium and the collar from synthetic rubber, both to British Standards. The collar is die-formed to the aluminium flashing

Advantages

- MacFlash is quickly and easily installed and offers cost savings in material and labour
- MacFlash is suitable for flat roofs and for roof pitches up to 45°
- MacFlash has special corrugations that can be easily dressed to form a seal
- MacFlash can be used with flue pipes from condensing boilers

	Nominal Pipe Size 4"/110mm pipe Base Measurements 18" x 18"		Nominal Pipe Size 3"/75mm pipe Base Measurements 18" x 18"	
	Code	RS1	Code	RS4
(MacFlash)	Nominal Pipe Size 4"/110mm pipe Base Measurements 18" x 24"		Nominal Pipe Size 2"/50mm pipe Base Measurements 18" x 18"	
laC	Code	RS2	Code	RS7
	Nominal Pipe Size 4"/110mm pipe Base Measurements 24" x 24"			
in	Code	RS3		
Aluminium Roof Flashing				









Flexible WC Connectors for Back to Wall WC Pans

		and reliable conne pan spigot prior t	ors provide a secure ection to the WC
		Inlet connections in soft synthetic re secured to the WC drive hose clip	
		 Flexible Connector use with all WC Pa misshaped outlet 	ans with a short or
		 Flexible Connector misalignment of p pipe 	ors allow for oan outlet and soil
		 Flexible Connector positioning and residue 	ors allow for easy emoval of WC Pan
Closed Position	Fully Extended Position		
	Closed	Extended	Code
90-114mm Inlet 4"/110mm Outlet	150mm	310mm	WC-F21R
90-114mm Inlet 3 ¹ /2"/90mm Outlet	150mm	310mm	WC-F21S

Flexible WC Connectors for Back to Wall WC Pans




celmac POLYGIENE ANTI VIRAL SEATS



Celmac is a leading brand of CME Sanitary Systems Limited, recognised throughout the world. The unique range of products within the Celmac Toilet Seat Collection is made possible by the combined manufacturing capabilities of specialist sites in England and abroad.

The Celmac toilet seats and covers shown below have been fully impregnated with Polygiene[™]. This is particularly important for use in hospitals, care homes, public buildings, fast food restaurants, hotel chains, airports, mass-transit facilities and other public areas as well as in domestic homes. Polygiene[™] contains pathogen killing properties which are proven to be effective in the control of SARS-coronavirus (SARS-CoV). Why take the risk - use Polygiene[™].



SMOOTH CLOSE SEATS





Concerto chrome plated smooth close hinge



Tango plastic colour matched smooth close hinge




Monarch chrome plated smooth close hinge

Manufactured using gel filled dampers, which allows the seat and cover to close slowly and silently without slamming. All the systems are equipped with a bypass system, which will stop any damage or breakage occurring should the seat or cover be forced shut against the smooth closing action, helps prevent children's fingers being caught.

Tango				Code
	 Polypropylene material Medium weight seat and wrap over domed cover Smooth close colour matched pre-assembled plastic hinges <i>Nominal weight 1.7kg</i> 	140-160mm	Seat and cover including smooth close plastic hinge	STG11WH
Maestro				Code
	 Thermoset material Total wrap over cover and distinctive European D shaped design Smooth close colour matched 	155mm	Seat and cover including smooth close hinge	SMA1SWH
	plastic hinge Nominal weight 2.3kg	355mm	Smooth close hinge	FSD11WH
Concerto				Code
	 Thermoset material Classic domed design Sturdy chrome plated brass smooth close hinge 	135-190mm	Seat and cover including smooth close hinge	SCO1SWH
	Nominal weight 2.1kg	375mm	Smooth close hinge	FUS11CP
Delta NE	N			Code
	 Thermoset material Overlaying 'sandwich' design cover and distinctive European D shaped design Chrome plated brass, smooth close hinges Easy clean Nominal weight 2.3kg 	100-165mm	Seat and cover including smooth close hinge	SWD1SWH
Monarch				Code
	 Polyester material Heavyweight seat and cover Sturdy chrome plated brass smooth close hinge Nominal weight 3.5kg 	140-160mm 490-442pm 430-442pm 400-4000000000000000000000000000000000	Seat and cover including smooth close chrome plated brass hinge	SMH1SWH

THERMOPLASTIC SEATS



FREEDOM SEATS






Mahogany


Pine

THERMOSET SEATS



THERMOSET SEATS






celmac THERMOSET SEATS

Neptune			Code
	Thermoset materialShell design, scalloped edged coverAdjustable colour matched	135-190mm Seat and cover including dual po plastic pillar hinge pack - FDP11-	
	 plastic hinges Easy to clean Nominal weight 1.8kg	Alternative hinge options: Colour matched plastic top fix	FTF11
		370mm Alternative hinge options: Stainless steel top fix hinge	FBH11SS
		Alternative hinge options: Universal bottom fix C/P brass h	inge FUN11CP
Hinges	Colour matched top fix plastic hinge pack FTF11	Stainless steel top fix	Universal bottom fix C/P brass hinge pack FUN11CP
Melody			Code
	Thermoset materialDished design coverEuropean styling	135-175mm Seat and cover including dual po plastic pillar hinge pack- FDP11-	
	Adjustable colour matched rodless concealed hinges Nominal weight 1.6kg	Alternative hinge options: Top fix quick release plastic	FQB11
		355mm Alternative hinge options: Stainless steel concealed hinge	FDR11SS
Hinges	Top fix quick release plastic hinge pack FQB11	Stainless steel concealed hinge pack FDR11SS	

celmac COMMERCIAL THERMOSET SEATS

Sonata			Code
Thermoset material BS1254 Type 1 Kitemark	135-190mm	Seat and cover including dual position plastic pillar hinge pack - FDP11	SSO11WH
 Stainless steel or plastic hinge options Seat only options available 		5 pack seats and covers individually bagged but in a single box - with FDP11 price individually but sold as 5	SSO21WH
Nominal weight 2.7kg	4	Seat only (no cover) including dual position plastic pillar hinge pack - FDP11	SSO51WH
BS1254 Type 1		5 pack seat only with plastic pillar hinge pack (FDP11) bagged but in a single box price individually but sold as 5	SSO61WH
Hinges Dual positional plastic pillar hinge pack FDP11		Seat and cover including stainless steel hinge - FSS11SS	SSO12WH
	-	Seat only (no cover) including stainless steel hinge - FSS11SS	SSO53WH
Colour matched top fix plastic hinge pack FTF11		Alternative hinge options: Colour matched plastic top fix	FTF11WH
Game Stainless steel	_	Alternative hinge options: Stainless steel top fix hinge	FBH11SS
top fix hinge pack FBH11SS		Alternative hinge options: Universal bottom fix C/P brass hinge	FUN11CP


COMMERCIAL THERMOSET SEATS



celmac COMMERCIAL THERMOSET SEATS

	Crescent Adult 'A	,			Code
		 Thermoset material in white and black Multiple stainless steel or plastic hinge options 	135-190mm	Seat and cover including dual position plastic pillar hinge pack - FDP11	SCR11WH
		Seat only optionSuitable for almost any WC panFor 14" and 16" WC pans	428-443mm	Seat and cover including stainless steel hinge - FSS11SS	SCR12WH
ŀ	Hinges	Nominal weight 2.7kg	395mm	Seat only (no cover) including dual position plastic pillar hinge pack - FDP11	SCR51WH
	Colour matched top fix plastic hinge pack	Non-cranked stainless steel hinge pack		Seat only (no cover) including stainless steel hinge - FSS11SS	SCR53WH
ŀ	FTF11	FSS11SS	-	Alternative hinge options: Colour matched plastic top fix	FTF11
_	plastic pillar hinge pack FDP11	pack FD211SS		Alternative hinge options: Stainless steel top fix hinge	FBH11SS
	Garanti Stainless steel top fix hinge pack FBH11SS	Stainless steel top fix hinge pack FBH11SS		Alternative hinge options: Universal bottom fix C/P brass hinge	FUN11CP
	Crescent Junior '	J'			Code
		 Thermoset material in white, black and red Stainless steel or plastic bigge entiops 	130-180mm	Seat only (no cover) including dual position plastic pillar hinge pack - FDP11	SCJ51WH
		hinge options • Suitable for 12" WC pans • Rigid and stable Nominal weight 1.1kg		Seat only (no cover) including stainless steel hinge - FSS13SS	SCJ53WH
			305mm	Alternative hinge options: Universal bottom fix C/P brass hinge	FUN11CP
				Alternative hinge options: Stainless steel top fix hinge	FBH11SS
	Hinges	Dual positional plastic pillar hinge pack FDP11	I fix hi	Inless steel top inge pack 11SS	

P72 Mini







Italian company with UNI EN ISO 9001 certifications, it has been manufacturing and marketing fittings for oil-hydraulics applications since 1952.

State-of-the-art production processes and highly advanced technologies that allow to keep top quality standards characterize the RASTELLI RACCORDI company of today, a recognized leader in the European and extra-European markets.

Three pieces straight coupling, M x F, NBR O-RING rubber seal



Art 604

Art 603

Three pieces elbow,	
M x F, NBR O-RING rubber seal	




Art 605

Five ways union




R"	3/8	1/2	3/4	I	1/4	1/2	2	
Box	-	-	-	10	-	-	-	



Art 605L

Five ways union fittings H 60 mm









Leading dimensions

R"	3/8	1/2	3/4	1	I 1/4	½	2
L	47	47	52	62	66	76	100



Leading dimensions R" 3/8 1/2 3/4 1 1/4 1 1/2 2 Т 45 50 60 69 80 92 120 L н 20 22 30 33 35 42 68 н






R"

R"

1/2M x 3/4F 3/4M x 1F

Art 612



Two union tails for water meter with gaskets



Art 615

Two union tails for water meter with gaskets



Art 850

Three pieces straight "EXCELSIOR" coupling, metal seat




Art 851

ADEI

ITAL

Three pieces elbow "EXCELSIOR" coupling, metal seat





Leading dimensions

1/2 x 1


R"

R"

3/4 x 1¼

R" X	D	L	BOX	R" X	D	L	BOX	R" X	D	L	BOX
3/8	15	58	58	1	25	82	15	11⁄2	40	105	6
1/2	15	58	58	1	30	92	10	2	50	125	6
1/2	18	65	65	1	32	95	10	2	60	140	5
1/2	20	65	65	1¼	30	93	10	21⁄2	60	135	5
3/4	20	67	67	1¼	32	95	10				
3/4	25	69	69	1¼	35	103	8				

| x |½



Leading dimensions

R" X	D	L	BOX	R" X	D	L	BOX	R" X	D	L	BOX
3/8	15	52	20	3/4	25	70	15	11⁄2	40	100	4
1/2	15	55	20	1	25	75	12	2	50	115	5
1/2	18	60	10	1	30	85	8	2	60	130	3
1/2	20	60	10	11⁄4	30	85	8	21⁄2	60	125	3
3/4	20	60	10	11⁄4	95	95	5				

1¼ x 2

I1⁄₂ x 21⁄₄

2 x 23/4



Art 956

Wall plate female elbow coupling



Art **959A**

Tube support for pipes S5 class



Art 957

"T" coupling



Leading dimensions					
R"	x	D			
1/2		20			
3/4		25			
1		32			

Lea	am	gai	mension
R'	'x	D	
1/2	2	20	
3/4	1	25	
1		32	

Leading dimensions

D x D x D

20
25
32



Leading dimensions D

Art 959B

NBR Brass Ogive, ring and NBR O-RING kit





Female "T" coupling



Leading dimensions					
D	x R"	хD			
20	1/2	20			
25	3/4	25			
32	1	32			
40	1¼	40			
50	11⁄2	50			
63	2	63			







R"

Box

1/2

20

3/4

15

I

10

| 1/4 | 1/2

Art 963

Male x female hexagonal reducing brass coupling



Art 964

Leading dimensions					
R"	X R"	BOX			
M 1/4	F 3/8	30			
M 3/8	F 1/2	25			
M 1/2	F 3/4	15			
M 3/4	F 1	10			
M 1	F 1¼	5			
M 1¼	F 1½	10			
M 1½	F 2	5			

Leading dimensions					
R"	1/2	3/4	1	I ¼	1 1/2
R" I	3/8	1/2	3/4	1	1 1⁄4
L	68	76	80	102	108
D	38	43	49	64	65
DI	45	50	61	65	67

Art 856

Bottom tank connection inside threaded





Female x female brass coupling



Art 961

Male x female hexagonal brass



Art 962



Leading dimensions

90° female x fer	male brass elbow



Art 965

90° male x female brass elbow




Art 966

90° female x female brass reducing elbow




R"	Х	R"	BOX
1/4		1/4	25
3/8		3/8	25
1/2		1/2	20
3/4		3/4	12
1		1	6
1¼		1¼	8
1½		1½	6
2		2	6

Leading dimensions					
R" X	R"	BOX			
1/4	1/4	40			
3/8	3/8	25			
1/2	1/2	30			
3/4	3/4	20			
1	1	12			
1¼	1¼	12			
11⁄2	11⁄2	10			
2	2	10			



coupling

F x F reducing brass coupling





Leading dimensions

R"	Х	R"	BOX	
1/4		1/4	25	
3/8		3/8	25	
1/2		1/2	20	
3/4		3/4	12	
1		1	6	
1¼		1¼	8	
1½		11⁄2	6	
2		2	6	

Leading dimensions

R"

1/2

3/4

1

1

BOX

_

20

12

6

6

R"

_

3/8

1/2

1/2

3/4

Х

Art 971

Four ways brass connection



Art **972**

Male x Male double brass nipple



5	R"	х	R"	BOX
	1/4		1/4	50
	3/8		3/8	40
	1/2		1/2	50
	3/4		3/4	30
	1		1	15
	11/4		11⁄4	15

11⁄2

2

10

6

11/2

2

Leading dimensions

Male x Male reducing double brass nipple



Art **974**

S.p.a

Art 973

Female brass plug



Leading	dimensions

	-
R"	BOX
1/4	50
3/8	50
1/2	40
3/4	20
1	15
1¼	10
1½	8
2	6



F x F x F brass reducing Tee

Leading dimensions R" X R" X R" BOX 3/4 1/2 3/4 10 3/4 5 1 1 11/4 1 11/4 6 11⁄2 1¼ 11⁄2 5 2 1½ 6 2

Leading dimensions

1/2 10

3/4 15

1 10

BOX

R" X R"

1/2

1

3/4



Art 970

F x F 3 pieces tapered brass pipe union, metal seat



M 1/2	F 3/4	12
M 3/4	F 1	6
M 1	F 1¼	8

Leading dimensions

R" X R" BOX

Leading dimensions R"XR"XR" BOX 1/4 1/4 20 1/4 3/8 3/8 3/8 20 1/2 1/2 1/2 15 3/4 3/4 3/4 12 1 6 1 1 11⁄4 1¼ 11⁄4 6 11/2 11⁄2 11⁄2 5

Art **967**

90° male x female brass reducing elbow



Art **968**

F x F x F brass Tee





FITTINGS FOR BLACK POLYETYLENE PIPE WITH BRASS SEAL

2

2 2 6

Stel rubinetterie

BOX

10

Leading dimensions

R"X R"X R"X R"

3/4

1

1/2 10

5

Exporting Company Ltd

Leading dimensions

1/4

3/8

1/2

3/4

1

1¼

11/2

BOX

40

25

15

20

10

10

6

R" X R"

3/8

1/2

3/4

1 1¼

1½

2



Art **979**

Threaded brass connection



Art **980**

Brass reducing extension M x F



Leading dimensions						
R"	Х	R"	BOX			
-		-	-			
3/8		1/2	30			
1/2		3/4	15			
3/4		1	10			

R"

BOX

15 3/4

10 3/4

10 1

10 1

10 1

10 1

20 1

10

10

L

30

40

50

60

80

100

12

15 15 1

20

30

L BOX

10

10

20

20

15

10

10

10

40

50

12

15

20

30

40

50

Leading dimensions

R"

1/2

1/2

1/2

1/2

1/2

1/2

3/4

3/4

3/4

3/4

BOX

30

30

20

15

15

25

20

15

T.

12 30

15

20

30

40

50

12

15

20 20

25

3/8

3/8

3/8

3/8

3/8

3/8

1/2

Art **981**

Brass extension M x F $_{R''}$



1/2 1/2 1/2

Art 982

M x M, threaded brass connection



Leading dimensions							
R"	3/8	1/2	3/4	I			
L	25	30	30	33			
Leadin R"	Leading dimensions						
ĸ	3/8	1/2	3/4	I			
D	50	50	20	20			
Box	50	50	30	20			

 R"
 BOX

 1/4
 50

 3/8
 50

 1/2
 40

 3/4
 20

 1
 15

 1¼
 10

 1½
 6

2 5

Leading dimensions








Art 975

Leading dimensions						
R"	х	R"	BOX			
3/8	;	1/4	50			
1/2		1/4	30			
1/2		3/8	50			
3/4	ļ	1/2	50			
1		3/4	25			
11⁄4		1	15			
1½		1¼	8			
2		1½	4			





Art 977 Ghiera in ottone Brass ring

Leading dimensions						
R"	х	R"	BOX			
	-		-			
3/8	-	1/2	50			
1/2	-	3/4	50			
3/4	-	1	25			
1	-	1¼	15			
1¼	-	11⁄2	10			



Art **978**

Brass ring with rim

Lead	din	g dir	nensi	ons
R"	х	R"	BOX	
	-		-	
3/8	-	1/2	50	
1/2	-	3/4	50	
3/4	-	1	25	
1	-	1¼	15	
1¼	-	1½	10	



Lead	ling d	imen	sions								
R"	L	BOX		R"	L	BOX			R"	L	BOX
1/2	60	15		3/4	60	10			1	60	10
1/2	80	10		3/4	80	8			1	80	10
1/2	100	8		3/4	100	6			1	100	6
1/2	120	8		3/4	120	6			1	120	6
1/2	150	8		3/4	150	6			1	150	4
	FITTI	NGS F	FOR BLACK P	OLYET	YLEN	E PIP	E WITH	BRAS	S SEA	۹L	



FITTINGS FOR BLACK POLYETYLENE PIPE WITH BRASS SEAL



Art 953

Elbow coupling

Art **950**

Straight coupling



			Leadi	ng di	mensions
			D ×	D	
			20	20	
المعمانية			25	25	
	-	mensions	32	32	
Dх	D		40	40	
20	20		50	50	
25	25		63	63	
32	32				
40	40				
50	50				
63	63				



Art **954**

Male elbow coupling

Art 951

Male straight coupling



			Leadi	ng di	mensions
			R" >	ĊD	
			1/2	20	
Leadi	na di	mensions	3/4	25	
R" >	-		1	32	
1/2	20		1¼	40	
			1½	50	
3/4	25		2	63	
1	32				
11⁄4	40				
11⁄2	50				
2	63				





Female elbow coupling

Art 952

Female straight coupling



			Leadi	ng di	mension
			R" >	< D	
			1/2	20	
			3/4	25	
			1	32	
Leadi	ng di	mensions	1¼	40	
R" :	хD		11⁄2	50	
1/2	20		2	63	
3/4	25				
1	32				
1¼	40				
11⁄2	50				
2	63				

ALL







Wall plate female elbow coupling





Tube support for pipes S5 class



Art 957

"T" coupling



Leading dimensions			
R" ×	D		
1/2	20		
3/4	25		
1	32		

Lead	IIn	g ai	mensio
R"	x	D	
1/2		20	
3/4		25	
1		32	

eau	ing ai	mensio
R"	хD	
1/2	20	
3/4	25	
1	32	

Leading dimensions

DD x D x D

Lead	lin	g di	mensio
R"	x	D	
1/2		20	
3/4		25	
1		32	

Leading	dimensions

	-
D	
20	
25	
32	
40	
50	



Art 959B

Brass Ogive, ring and NBR O-RING kit



Art 958

Female "T" coupling



Lead	dir	ng d	imer	nsions
D	x	R"	хD	
20		1/2	20	
25		3/4	25	
32		1	32	
40		1¼	40	
50		11⁄2	50	
63		2	63	

Leading dimensions







FITTINGS FOR BLACK POLYETYLENE PIPE WITH BRASS SEAL





TNJ Pipeclips is a UK based business specialising in the supply of pipe clips and brackets to the plumbing and electrical trade.

Their extensive range includes products made in the following materials Cast Brass, Pressed Brass, Copper, Malleable Iron, Plastic and steel. All brass and copper products are available in self colour or chrome plated.

Malleable Iron

Screw On	Brackets	Code - M3
	S/C Galv	
1/2"		
3/4"	0	
1"		
1.1/4"		
1.1/2"		
2"	-	
2.1/2"		
3"	JC	
4"		

S/C = Self Colour Malleable (Black)

Single and Double Rings Tapping is as follows: 1/2" up to 2" = M10 2.1/2" up to 6" = M12

** Special deals available on large quantities of Various sizes of BSP - Please Enquire **

Single Rings M10 & M12	2 Code - M4	Double Rin
S/C 0	Galv	
1/2"		1/2"
3/4"		3/4"
1"		1"
1.1/4"		1.1/4"
1.1/2"		1.1/2"
2"		2"
2.1/2"		2.1/2"
3"		3"
4"		4"
5"		5"
6"		6"
Backplate - Female		Code - M6

S/C















On Brackets 0

35mm

42mm

54mm

J.

Brass

Screw On Brackets	DI	155	
Cast Brass	Code - CB3	Pressed Brass	Code - PB
15mm22mm28mm35mm42mm54mm67mm76mm108mm		15mm22mm28mm35mm42mm54mmBrassChrome	
Cast Brass Munsen Rings			
Single Rings - M10	Code - HS1	Double Rings - M10	Code - HS
12mm15mm22mm28mm35mm42mmBrassChrome	54mm 67mm 76mm 108mm 133mm 159mm	12mm15mm22mm28mm35mm42mm	54mm 67mm 76mm 108mm 133mm 159mm
Cast Brass Back Plates		Mala	
Female	Code - CB10F	Male	Code - CB10N
M10 Tapped Round Base Wall Brackets	I M10 as Standard	M10 - A M10 - B * Type B has an exte	nded boss*
Cast Brass - Short Stem	Code - WB6	Cast Brass Dual Purpose C	ode - WB7 (1/4 Bsp
15mm 22mm 28mm 35mm 42mm 54mm		15mm 22mm 28mm 35mm 42mm 54mm	
Hospital Brackets & Connectir Hospital Brackets	Code - HB1	Connecting Tubes x 2"	Code - Con
15mm 22mm 28mm 35mm 42mm 54mm		1/8"	
Copper	0.1.00		
Copper 2 Piece Spacing Clip	Code - C2	Copper Saddle Bands	Code - C
8 &15mm 22mm 28mm 25mm		6 -12mm 22mm 28mm	



For more information on any of these products, please email: enquiries@wgreerltd.co.uk

35mm

42mm

54mm

0 10





Plastic

		Code - C07	Double Clips	Code - C13
15mm 22mm 28mm	N		15x15mm 15x22mm 22x22mm	
		Code - C08	Single Hinged Pipe Clip (Interlocking)	Code - C14
15mm 22mm 28mm	5		15mm 22mm 28mm	
		Code - C10	Double Hinged Pipe Clip (Interlocking)	Code - C15
15mm 22mm 28mm			15mm 22mm 28mm	
Nail Clip		Code - C11	Plastic Double Snap On	Code - C16
7-8mm 10-12mm 15mm 22mm 28mm	Q		15-15mm 15-22mm 22-22mm	
Slip-On Clip		Code - C12	Top Hat Washers	Code - C17
12.7mm 15.0mm 17.5mm 19.0mm 23.0mm 25.4mm			1/2" 3/4" Polyproplylene Plumbing Washer 1.1/2X7/8" 1/2" Pillar Tap	Code - C18
27.5mm 31.7mm 34.mm 38.1mm 42.mm 42.6mm 44.4mm 48.7mm 53.9mm 60.5mm	5		1.3/4"x1.1/8" 3/4" Pillar Tap 2.1/4"x 1.11/32" 1" Tank Connections 2.3/8"x1.11/16" 1.1/4" Lav Waste 3x1.11/16" 1.1/4" Bath Waste 3.1/4"x1.15/16" 1.1/2" Bath Waste 3.1/2"x1.15/16" 1.1/2 Sink Waste 3.1/2"x1.11/16" 1.1/4" Sink Waste	







Brass Backnuts / Bushes Etc

Hex Nipples Taper Thread BSP	Code - BN1	Plugs Hex Head Flange BSP	Code - BN4
1/2" 3/4" 1"		1/2" 3/4" 1" 1.1/4"	
Backnuts BSP	Code -BN2	Divers Covers Lissed DCD	Cada DNE
1/2" 3/4" 1" 1.1/4"		Plugs Square Head BSP 3/4" Blank Caps BSP	Code - BN5 Code - BN6
1.1/2" 2" Reducing Bushes Hex BSP	Code - BN3	1/2" 3/4" 1"	
		1.1/4"	
1/4"x1/8" 3/8"x1/4" 3/8"x1/8"		Immersion Heater Rings& Plugs	Code - BN7/8
1/2"x3/8" 1/2"x1/4" 1/2"x1/8"		Plug - BN7 Ring - BN8	
3/4"x1/2"		Radiator Bleed Valves	Code - BN9
1"x3/4" 1"x1/2" 1.1/4"x1" 1.1/4"x3/4" 1.1/4"x1/2"		1/8" 1/4" 1/2"	
1.1/2"x1.1/4"		Radiator Key	Code - BN10
1.1/2"x1" 1.1/2"x3/4" 1.1/2"x1/2"		T	
2"x1.1/2"		Brass or Steel Adaptors	Code - BN11
2"x1.1/4" 2"x1" 2"x3/4" 2"x1/2"		1/4" x M10 3/8" x M10 3/8" x M12 1/2" x M10 1/2" x M12	





Float switch and level indicator manufacutrers

George Lancaster (International) Limited have been manufacturing REMEX FLOAT SWITCHES since 1985

REMEX FLOAT SWITCHES are specifically designed for the automatic control of all types of electrically driven pumps, alarm systems and indicators where a rise or fall of any form of liquid is required, or where tanks require automatic emptying or filling.

Remex Type "B01"

Technical Data	a			
Specifications	Liquid Temperature:	0 to 60 c	legrees C	
	Contact Rating:	AC, 10 A	AMP, 250V	
	Switching Differential:	200		T
Weight	<i>Cable Length</i> 3 m. 5 m. 10 m. 20 m.	Weight o 0.7 kg 1.0 kg 1.5 kg 2.0 kg	of B-01 Float Switch GREER Exporting Company Ltd	

Chemical Resistance

Acids	Acetic Acid 50% & 70% Benzoic Acid	Boric Acid Citric Acid	Acid Solution (5%) Tannic Acid
Bases	Ammonium Hydroxide Sodium Hydroxide	Potassium Hydroxide Calcium Hydroxide	
Salts	Aluminium Chloride	Ferrous Sulphate	Sodium Nitrate
	Calcium Sulphate	Magnesium Chloride	Sodium Bicarbonate
	Calcium Chloride	Potassium Sulphate	Sodium Carbonate
	Calcium Nitrate	Potassium Nitrate	Zinc Sulphate
	Copper Chloride	Potassium Bicarbonate	Zinc Chloride
	Copper Sulphate	Sodium Sulphate	
	Ferric Chloride	Sodium Chloride	
Solvents	Formaldehyde 37%	Methyl Alcohol	
Gases	Carbon Dioxide	Carbon Monoxide	



For more information on any of these products, please email: enquiries@wgreerltd.co.uk





Remex Type "P"

Technical Data

5 or 10 amp - 220V - 440V - Single Pole Special consideration has been given to the spring movement resulting in exceptional equal balance, the special choice of material for the spindle results in the prevention of any seizing. Minimum liquid variation 1.25" (32mm)

Float

A weight balanced float that can be used in temperatures up to 80 degrees C (158F).

Nylon Plated Cord

A 3 feet (0.9m) is available as standard but longer lengths are available. This is impervious to most liquids and is fixed with a stainless steel spring hook.

Stops

These are adjustable non slip stainless steel spring stops specially designed for the Remex Type "P".

Weights

A.B.S. thermoplastic encases the weight and counterweight. This is ideally suited for installation where hygiene is a prime requirement.



Chemical Resistance

Acids	Acetic Acid 50% & 70%	Boric Acid	Acid Solution (5%)
	Benzoic Acid	Citric Acid	Tannic Acid
Bases	Ammonium Hydroxide	Potassium Hydroxide	
	Sodium Hydroxide	Calcium Hydroxide	
Salts	Aluminium Chloride	Ferrous Sulphate	Sodium Nitrate
	Calcium Sulphate	Magnesium Chloride	Sodium Bicarbonate
	Calcium Chloride	Potassium Sulphate	Sodium Carbonate
	Calcium Nitrate	Potassium Nitrate	Zinc Sulphate
	Copper Chloride	Potassium Bicarbonate	e Zinc Chloride
	Copper Sulphate	Sodium Sulphate	
	Ferric Chloride	Sodium Chloride	
Solvents	Formaldehyde 37%	Methyl Alcohol	
Gases	Carbon Dioxide	Carbon Monoxide	



GEORGE LANCASTER (INTERNATIONAL) LIMITED

Float switch and level indicator manufacutrers



Remex Type "C"



Float Equipment

Polythene Float (standard): 5" in diameter, these are injection moulded for liquid temperatures up to 55-60 C. They can be used for weak acids and oils but not suitable for hot detergents.

Copper Float: 5" in diameter, brazed or soldered at the seams. For continuous immersion in boiling water. They are also suitable for certain liquids such as oils or solvents up to 100 degrees C.

Stainless Steel: 5" in diameter also suitable for oils and solvents and hot water and return condensates. The added advantage of such a float is if hygiene is required.

Chain Equipment

A 3 feet (0.9m) length of brass chain is available as standard on all die-cast Remex switches. However longer lengths are available to customers' requirements.

Weight Equipment

Enamelled cast iron weights and counterweights are provided as standard and further weights can be added if required.

Stop Equipment

Adjustable stainless steel float stops are provided as standard to suit all operations.

Rod Equipment

Copper Rods: 6.3mm in diameter rods are available in lengths 3 - 10 feet (0.9 - 3m) with properly balanced weight to match the counterweight. A rod operation is recommended for use where there is a turbulence or sludge, e.g. septic tanks.

Stainless steel rods: the added security of stainless steel would be suitable for hygiene purposes. Lengths range from 3 - 10 feet (0.9 - 3m).









Ph. +44 (0) 1450 860 642 Ph. +44 (0) 208 133 6521

FII: +44 (0) 208 133 0321

Fax. +44 (0) 1450 860 258

email:

enquiries@greer-exporting.co.uk

